

Title (en)

Thermal head printer and process for printing substantially light-insensitive recording materials.

Title (de)

Thermokopfdruker und Verfahren zum Drucken auf thermographischen Aufzeichnungsmaterialien

Title (fr)

Imprimante à tête thermique et et procédé d'impression sur matériaux d'impression thermographiques

Publication

EP 1457345 A1 20040915 (EN)

Application

EP 04100796 A 20040301

Priority

- EP 04100796 A 20040301
- EP 03100622 A 20030312

Abstract (en)

A thermal head printer with image-invariant printing speeds for printing a substantially light-insensitive thermographic material having a print density-driving power level characteristic, the thermal head printer comprising a transport means, one or more thermal heads each having an array of heating elements, a thermal print head drive system capable of supplying power to each of the printing elements, and a calibration means based on the print density-driving power level characteristic of the thermographic material; a process for calibrating a thermal head printer with image-invariant printing speeds, the thermal head printer comprising one or more thermal heads each having an array of heating elements connected to a power supply capable of supplying a given number of heating element driving power levels from 0 to a maximum driving power level number, corresponding to Pmax, to each heating element for printing a substantially light-insensitive thermographic material by image-wise heating the thermographic material with the heating elements, the process comprising the steps of: (i) putting the printer into a calibration mode; (ii) printing one or more step-wedges of print densities by heating the thermographic material with the heating elements at different DPLN's; (iii) determining the optical density of each step of the step-wedge(s) of print densities with a densitometer thereby obtaining the dependence of the print density upon DPLN; (iv) deriving from the dependence, or all the dependences of the print density upon DPLN, a single smoothed dependence of the rate of change of print density, D, with DPLN, DELTA D/ DELTA DPLN, as a function of DPLN for the thermographic material; (v) establishing a threshold rate of print density change per DPLN for the specific thermographic material being printed; and (vi) setting up the thermal head printer so that the threshold rate of print density increase per DPLN cannot be undercut; and a process for printing a substantially light-insensitive thermographic material with a thermal head printer comprising one or more thermal heads each having an array of heating elements connected to a power supply capable of supplying a given number of heating element driving power levels from 0 to a maximum driving power level number, corresponding to Pmax, the process comprising the steps of: calibrating the thermal head printer according to the above-described calibration process, transporting the substantially light-insensitive thermographic material past the thermal head, and image-wise heating of the substantially light-insensitive thermographic material by means of the heating elements.

IPC 1-7

B41J 2/36; **B41J 2/375**

IPC 8 full level

B41J 2/36 (2006.01); **B41J 2/375** (2006.01)

CPC (source: EP)

B41J 2/36 (2013.01); **B41J 2/375** (2013.01)

Citation (search report)

- [XAY] EP 0922585 A2 19990616 - FUJI PHOTO FILM CO LTD [JP]
- [YA] US 4939581 A 19900703 - SHALIT HANOCH [US]
- [XDA] EP 0453714 A1 19911030 - MITSUBISHI ELECTRIC CORP [JP]
- [XA] US 6411318 B1 20020625 - SAWANO MITSURU [JP], et al
- [AD] EP 1247654 A1 20021009 - AGFA GEVAERT [BE]
- [A] EP 1006404 A1 20000607 - AGFA GEVAERT [BE]

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

EP 1457345 A1 20040915; **EP 1457345 B1 20091230**

DOCDB simple family (application)

EP 04100796 A 20040301