

Title (en)

Pipe socket joint secured against decoupling

Title (de)

Zuggesicherte Muffenrohrverbindung

Title (fr)

Raccord à manchon de tuyaux sécurisé contre découplage

Publication

**EP 1460325 A3 20041201 (DE)**

Application

**EP 04001398 A 20040123**

Priority

DE 10306316 A 20030215

Abstract (en)

[origin: EP1460325A2] Two pipes are joined with a sleeve fit. The interface zone between the two pipes is closed by an O-ring seal consisting of a first section of relatively hard material (H) and a second section of softer material (D). The seal is a one-piece unit. The hard section incorporates an essentially narrow U-shaped circular groove (15), while the soft section incorporates an essentially wide U-shaped groove (14) at right angles to the first (15).

IPC 1-7

**F16L 21/08**

IPC 8 full level

**F16L 21/08** (2006.01); **F16L 37/088** (2006.01)

CPC (source: EP US)

**F16L 21/08** (2013.01 - EP US); **F16L 37/088** (2013.01 - EP US)

Citation (search report)

- [DX] US 3684320 A 19720815 - PLATZER HERBERT, et al
- [X] US 4303262 A 19811201 - PIERREL MICHEL, et al
- [A] FR 1168647 A 19581211 - CIE DE PONT A MOUSSON

Cited by

JP2009541686A; EP1739334A1; EA014478B1; EP3601864A4; US7806445B2; WO2008000472A3; WO2015011454A1; EP2194306A2; WO2024037718A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT RO SE SI SK TR

DOCDB simple family (publication)

**EP 1460325 A2 20040922**; **EP 1460325 A3 20041201**; **EP 1460325 B1 20091111**; AT E448438 T1 20091115; DE 10306316 A1 20040826; DE 10306316 B4 20050331; DE 502004010334 D1 20091224; ES 2336555 T3 20100414; SI 1460325 T1 20100430

DOCDB simple family (application)

**EP 04001398 A 20040123**; AT 04001398 T 20040123; DE 10306316 A 20030215; DE 502004010334 T 20040123; ES 04001398 T 20040123; SI 200431338 T 20040123