

Title (en)  
Fire-proof construction of a thatched roof

Title (de)  
Feuerbeständige Reet-Dacheindeckungskonstruktion

Title (fr)  
Construction de toit en chaume résistante au feu

Publication  
**EP 1464772 B1 20070718 (EN)**

Application  
**EP 04007742 A 20040331**

Priority  
DK PA200300496 A 20030401

Abstract (en)  
[origin: EP1464772A1] The present invention concerns a roof construction (20) for a thatched roof (30) with side edges (47), eaves (24) and ridge (27), including a glass matting (23) placed on the laths (22) of the roof construction (20), preferably covering the entire roof construction (20), and a mineral wool mat (25) disposed between the thatched roof (30) and the glass matting (23) along the side edges (47) and eaves (24) of the thatched roof (30), where along the ridge (27) of the thatched roof (30) between the thatched roof (30) and the glass matting (23) furthermore there is placed a mineral wool mat (28) having a melting point of 800 DEG C or higher. <IMAGE>

IPC 8 full level  
**E04D 9/00** (2006.01)

CPC (source: EP)  
**E04D 9/00** (2013.01)

Citation (examination)  
TOFTE, SOEREN: "Oplaegningsvejledning for SEPATEC brandsikringssystem", 29 September 2003

Cited by  
EP3741923A1; EP2236690A4; WO2022037840A1

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PL PT RO SE SI SK TR

Designated extension state (EPC)  
LT LV

DOCDB simple family (publication)  
**EP 1464772 A1 20041006; EP 1464772 B1 20070718**; AT E367491 T1 20070815; DE 602004007565 D1 20070830;  
DE 602004007565 T2 20080417; DK 1464772 T3 20071105; PL 1464772 T3 20071231

DOCDB simple family (application)  
**EP 04007742 A 20040331**; AT 04007742 T 20040331; DE 602004007565 T 20040331; DK 04007742 T 20040331; PL 04007742 T 20040331