

Title (en)
Lock

Title (de)
Schloss

Title (fr)
Serrure

Publication
EP 1464782 A3 20070509 (DE)

Application
EP 04001886 A 20040129

Priority
DE 20305649 U 20030402

Abstract (en)
[origin: EP1464782A2] Lock for a locking device for windows, doors, etc. comprises a lock housing (12), a locking bar (14) movably arranged in the lock housing, and a drive rod (16) driving the locking bar. The drive rod is connected to a holding device (26), which locks the drive rod in both end positions. Preferred Features: The holding device is spring-loaded and made of plastic. The spring (30) is supported on the rear wall (32) of the lock housing. The drive rod has a finger (36) protruding at an angle from the plane of the drive rod and engaging in the holding device. The holding device has a guide for the drive rod.

IPC 8 full level
E05C 9/18 (2006.01); **E05B 15/00** (2006.01)

CPC (source: EP)
E05C 9/1841 (2013.01); **E05B 15/0053** (2013.01)

Citation (search report)

- [X] US 5524942 A 19960611 - FLEMING PAUL D [US]
- [X] GB 2119013 A 19831109 - FIXFABRIKEN AB
- [X] EP 0099292 A2 19840125 - ROCHMAN ZVI HENRI
- [A] EP 0173987 A1 19860312 - HOERMANN KG FREISEN [DE]

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT RO SE SI SK TR

Designated extension state (EPC)
AL LT LV MK

DOCDB simple family (publication)
EP 1464782 A2 20041006; EP 1464782 A3 20070509; EP 1464782 B1 20090107; AT E420264 T1 20090115; DE 20305649 U1 20030618; DE 502004008805 D1 20090226

DOCDB simple family (application)
EP 04001886 A 20040129; AT 04001886 T 20040129; DE 20305649 U 20030402; DE 502004008805 T 20040129