

Title (en)  
Lighting device

Title (de)  
Beleuchtungsanordnung

Title (fr)  
Dispositif d'éclairage

Publication  
**EP 1467139 B1 20100512 (DE)**

Application  
**EP 04008208 A 20040405**

Priority  
AT 5332003 A 20030407

Abstract (en)  
[origin: EP1467139A2] The arrangement has at least one linear light source (1) essentially fully within a light conductor (3) and at least two reflectors (2) at the light outlet openings (16) of the light conductor for bounding the angular range of radiation. There are at least two reflectors on one side of the light source at different distances and arranged so that their main beam direction is essentially perpendicular to the longitudinal direction of the linear light source.

IPC 8 full level  
**F21S 8/00** (2006.01); **F21V 5/02** (2006.01); **F21V 7/00** (2006.01); **F21V 11/02** (2006.01); **F21V 11/06** (2006.01); **F21V 13/02** (2006.01); **F21V 23/02** (2006.01)

CPC (source: EP US)  
**F21V 5/02** (2013.01 - EP US); **F21V 7/0008** (2013.01 - EP); **F21V 7/0016** (2013.01 - EP); **F21V 7/0058** (2013.01 - EP); **F21V 11/02** (2013.01 - EP); **F21V 11/06** (2013.01 - EP US); **F21V 23/02** (2013.01 - EP); **F21W 2131/402** (2013.01 - EP); **F21Y 2103/00** (2013.01 - EP US)

Cited by  
WO2010051226A1; GB2478667A; GB2478667B; US9052083B2

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)  
**EP 1467139 A2 20041013; EP 1467139 A3 20070704; EP 1467139 B1 20100512**; AT 500432 A1 20051215; AT 500432 B1 20060315; AT 500432 B8 20070215; AT E467796 T1 20100515; DE 502004011146 D1 20100624

DOCDB simple family (application)  
**EP 04008208 A 20040405**; AT 04008208 T 20040405; AT 5332003 A 20030407; DE 502004011146 T 20040405