

Title (en)  
Angular position detector

Title (de)  
Winkelstellungsdetektor

Title (fr)  
Décteur de position angulaire

Publication  
**EP 1467184 A2 20041013 (EN)**

Application  
**EP 03012601 A 20000615**

Priority

- EP 00112683 A 20000615
- JP 17165099 A 19990617
- JP 17165199 A 19990617
- JP 24430699 A 19990831

Abstract (en)  
An angular position detection apparatus, which can improve a detection accuracy of the angular position by improving a linearity of an output characteristic with respect to an angular position detection apparatus, and to downsize an outer size thereof. A permanent magnet (27) is fixed to a side surface of a rotor core (24), which integrally rotates with a detection target object. An inner surface of a cylindrical portion (26) of the rotor core is closely confronted with an outer surface of a stator core (25). Thus, the angular position detection apparatus is formed as a radial gap type in which magnetic flux is gone through an air gap G1 between the cylindrical portion and the stator core along a radial direction. A magnetic flux detection gap portion (30) is formed at a center portion of the stator core so as to go through toward a diametral direction. A Hall IC (31) is arranged in the magnetic flux detection gap portion. The permanent magnet is magnetized so that lines of magnetic force therein are parallel with each other. As a result, it can expand the range, in which the magnetic flux density in the magnetic flux detection gap portion linearly changes in proportion to the angular position of the rotor core, and it can improve the linearity of output characteristic of the Hall IC with respect to the angular position.

IPC 1-7  
**G01D 5/14**

IPC 8 full level  
**G01D 5/14** (2006.01); **F02D 11/10** (2006.01)

CPC (source: EP US)  
**G01D 5/145** (2013.01 - EP US); **F02D 11/106** (2013.01 - EP US)

Cited by  
CN102869954A; US9841296B2; US8111064B2; WO2011139469A1; WO2007122055A1

Designated contracting state (EPC)  
DE FR GB

DOCDB simple family (publication)  
**EP 1061341 A2 20001220**; **EP 1061341 A3 20030507**; EP 1467184 A2 20041013; EP 1467184 A3 20120215; US 6483296 B1 20021119

DOCDB simple family (application)  
**EP 00112683 A 20000615**; EP 03012601 A 20000615; US 58977200 A 20000609