

Title (en)
HOIST

Title (de)
HEBEVORRICHTUNG

Title (fr)
APPAREIL DE SUSPENSION

Publication
EP 1483192 A1 20041208 (EN)

Application
EP 03712328 A 20030307

Priority
• GB 0300988 W 20030307
• GB 0205899 A 20020313

Abstract (en)
[origin: WO03078294A1] A retainer has a sleeve (3) urged to a locking position covering a hook opening, by a spring. In use, to attach an accessory, for example, a spreader bar (2) to the hoist (1) lifting arm (1) the hook (4) of the retainer sleeve is slid over a pivot pin (9) of the hoist lifting arm (1) and locking sleeve (3) is urged by spring (7) to a locking position preventing the escape of the pivot pin (9) from the hook (4). To unlock the spreader bar (2) from the hoist lifting arm (1), the retainer sleeve (3) is pushed downwards to disengage the hook (4) from the pivot pin (9). The retainer can be used to enable easy use and dismantling of hoist accessories without removing any components or requiring tools.

IPC 1-7
B66C 23/66; **B66C 3/00**

IPC 8 full level
B66C 1/00 (2006.01); **B66C 3/00** (2006.01)

CPC (source: EP)
B66C 1/10 (2013.01); **B66C 1/68** (2013.01); **B66C 3/005** (2013.01)

Citation (search report)
See references of WO 03078294A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT RO SE SI SK TR

DOCDB simple family (publication)
WO 03078294 A1 20030925; AT E342864 T1 20061115; AU 2003217006 A1 20030929; DE 60309137 D1 20061130; DE 60309137 T2 20070906; EP 1483192 A1 20041208; EP 1483192 B1 20061018; GB 0205899 D0 20020424; GB 0305178 D0 20030409; GB 2386593 A 20030924; GB 2386593 B 20040811; TW 200305539 A 20031101

DOCDB simple family (application)
GB 0300988 W 20030307; AT 03712328 T 20030307; AU 2003217006 A 20030307; DE 60309137 T 20030307; EP 03712328 A 20030307; GB 0205899 A 20020313; GB 0305178 A 20030307; TW 92105480 A 20030313