Title (en)

METHOD FOR CONTROLLING A WINDOW-BASED USER INTERFACE AND AN HMI DEVICE FOR CARRYING OUT SAID METHOD

Title (de)

VERFAHREN ZUR STEUERUNG EINER FENSTERORIENTIERTEN BEDIENOBERFLÄCHE UND EIN HMI GERÄT ZUR DURCHFÜHRUNG DES VERFAHRENS

Title (fr)

PROCEDE DE COMMANDE D'UNE INTERFACE UTILISATEUR A FENETRES ET APPAREIL A INTERFACE HOMME-MACHINE POUR REALISER CE PROCEDE

Publication

EP 1495399 A2 20050112 (DE)

Application

EP 03734647 A 20030116

Priority

- DE 0300110 W 20030116
- DE 10203370 A 20020129

Abstract (en)

[origin: DE10203370A1] The invention relates to the control of a window-based, interactive user interface (210) comprising at least two overlapping display and control windows (220, 230). When one display and control window (220) is activated, the other display and control window (230) is automatically reduced in size to such an extent that it is represented in its entirety on the interactive user interface (210), without overlapping the display and control window (220). Preferably, the activation of the display and control window (220) is triggered by an optical cursor (211).

IPC 1-7

G06F 9/44

IPC 8 full level

G06F 9/44 (2006.01); **G06F 9/451** (2018.01); **G09G 5/00** (2006.01)

CPC (source: EP US)

G06F 9/451 (2018.01 - EP US)

Citation (search report)

See references of WO 03065208A2

Citation (examination)

OTTINO C: "WINDOWS USAGE IN A PLANT AUTOMATION SYSTEM", ISA TRANSACTIONS, INSTRUMENT SOCIETY OF AMERICA. PITTSBURGH, US, vol. 33, no. 3, 1 September 1994 (1994-09-01), pages 227 - 233, XP000468457, ISSN: 0019-0578, DOI: 10.1016/0019-0578(94)90094-9

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT SE SI SK TR

DOCDB simple family (publication)

DE 10203370 A1 20030731; EP 1495399 A2 20050112; US 2005055646 A1 20050310; US 7418669 B2 20080826; WO 03065208 A2 20030807; WO 03065208 A3 20041028

DOCDB simple family (application)

DE 10203370 A 20020129; DE 0300110 W 20030116; EP 03734647 A 20030116; US 90132704 A 20040729