

Title (en)

Method and apparatus for using a close proximity probe for optical communication with a device external to the probe

Title (de)

Verfahren und Vorrichtung für die Benützung eines Näherungssensors in einer optischen Übertragung mit einer Einrichtung ausserhalb des Sensors

Title (fr)

Méthode et appareil pour utiliser une sonde de proximité dans une communication optique avec un dispositif externe à la sonde

Publication

EP 1503525 A2 20050202 (EN)

Application

EP 04017710 A 20040727

Priority

US 62822603 A 20030728

Abstract (en)

An optical communication probe enables a diagnostic tool to optically communicate with an external device, such as an appliance, through a low intensity indicator light of the external device. The communication probe includes an optical transmitter and an optical receiver mounted within a housing. The optical transmitter is a high intensity light emitting diode (LED) and the optical receiver is a sensitive phototransistor. The high intensity LED helps compensate for the relatively high optical threshold of a standard photodetector or LED used as an optical receiver at the appliance and the sensitive phototransistor helps compensate for the relatively low intensity light generated by the indicator light of an appliance. <IMAGE>

IPC 1-7

H04B 10/10; **H04B 10/24**

IPC 8 full level

H04B 10/08 (2006.01); **H04B 10/24** (2006.01)

CPC (source: EP US)

H04B 10/40 (2013.01 - EP US)

Cited by

EP2087288A4; CN110840367A; WO2007048005A3

Designated contracting state (EPC)

DE FR GB IT

DOCDB simple family (publication)

EP 1503525 A2 20050202; **EP 1503525 A3 20051221**; CN 1617468 A 20050518; US 2005025493 A1 20050203

DOCDB simple family (application)

EP 04017710 A 20040727; CN 200410087430 A 20040728; US 62822603 A 20030728