

Title (en)

Method for protecting an axle of a railway vehicle, corresponding axle, and bogie with such an axle.

Title (de)

Verfahren zum Beschützen der Radachse eines Schienenfahrzeuges, entsprechende Radachse, und Drehgestell dieser Achse.

Title (fr)

Procédé de protection d'un essieu de véhicule ferroviaire, essieu et bogie de véhicule ferroviaire correspondants

Publication

EP 1508455 B1 20090121 (FR)

Application

EP 04300447 A 20040716

Priority

FR 0310071 A 20030821

Abstract (en)

[origin: EP1508455A1] The procedure for protecting a railway vehicle bogie axle (6) consists of rolling a strip (10) of a supple polymer material cut from a large sheet and having a preferable thickness of 8 - 10 mm round each of the axle zones (2) to be protected and fixing it in place. The two ends (10 1, 10 2) of each strip are chamfered, and grooves (12) are made in its inner surface. The strips are held in place by mechanical means, e.g. stainless steel collars.

IPC 8 full level

B60B 37/04 (2006.01); **B61F 5/50** (2006.01); **F16D 3/84** (2006.01)

CPC (source: EP)

B61F 5/50 (2013.01)

Cited by

CN102770323A; DE102012205220A1; EP1942040A1; FR2911102A1; IT201600081794A1; CN109641598A; JP2019527649A; US10836409B2; US9238472B2; WO2018025198A1; WO2012007001A1; EP2539199B1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

EP 1508455 A1 20050223; **EP 1508455 B1 20090121**; AT E421433 T1 20090215; DE 602004019166 D1 20090312; ES 2320764 T3 20090528; FR 2858960 A1 20050225; FR 2858960 B1 20050930

DOCDB simple family (application)

EP 04300447 A 20040716; AT 04300447 T 20040716; DE 602004019166 T 20040716; ES 04300447 T 20040716; FR 0310071 A 20030821