

Title (en)
DAMPING APPARATUS

Title (de)
DÄMPFUNGSEINRICHTUNG

Title (fr)
APPAREIL AMORTISSEUR

Publication
EP 1509441 A1 20050302 (EN)

Application
EP 02741168 A 20020531

Priority
IT 0200355 W 20020531

Abstract (en)
[origin: WO03101816A1] A damping apparatus with excellent endurance that has a simple structure and can be produced at a low cost is provided. The damping apparatus comprises linking means 21 for linking the driven sprocket 11 of chain transmission apparatus 10 of a motor two-wheel vehicle to the hub 2, which serves as an installation member therefor, so as to allow for a relative rotation thereof within a specific angular range; a base plate 22 inserted between the driven sprocket 11 and hub 2 so that it cannot rotate with respect to the hub 2; a plurality of receptacles 2a, 11a, 22a formed some distance apart from each other in the circumferential direction on the facing surfaces of hub 2, driven sprocket 11, and base plate 22; and elastic members 23 placed into the receptacles 2a, 11a, 22a and absorbing the impact forces acting between the driven sprocket 11 and hub 2 by elastic deformation between the edges of receptacles 11a of driven sprocket 11 in the circumferential direction and the opposite edges of receptacles 2a, 22a of hub 2 and base plate 22 in the circumferential direction.

IPC 1-7
B62M 7/00; **B62M 9/00**; **F16H 55/14**; **F16H 55/30**

IPC 8 full level
B62M 7/00 (2010.01); **B62M 9/00** (2006.01); **F16H 55/14** (2006.01); **F16H 55/30** (2006.01)

CPC (source: EP)
B62M 7/00 (2013.01); **B62M 9/00** (2013.01); **F16H 55/14** (2013.01); **F16H 55/30** (2013.01); **F16H 2055/306** (2013.01)

Citation (search report)
See references of WO 03101816A1

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)
WO 03101816 A1 20031211; AU 2002314530 A1 20031219; EP 1509441 A1 20050302

DOCDB simple family (application)
IT 0200355 W 20020531; AU 2002314530 A 20020531; EP 02741168 A 20020531