Title (en)

HYDRAULICALLY ACTUATED, VARIABLE VALVE GEAR OF AN INTERNAL COMBUSTION ENGINE

Title (de

HYDRAULISCH BETÄTIGTER, VARIABLER VENTILTRIEB EINER BRENNKRAFTMASCHINE

Title (fr)

MECANISME DE DISTRIBUTION VARIABLE A ACTIONNEMENT HYDRAULIQUE D'UN MOTEUR A COMBUSTION INTERNE

Publication

EP 1509685 A1 20050302 (DE)

Application

EP 03737957 A 20030425

Priority

- DE 10224038 A 20020531
- EP 0304294 W 20030425

Abstract (en)

[origin: WO03102383A1] The invention relates to a hydraulically actuated, variable valve gear (1) of an internal combustion engine, comprising a master piston (3), which is in contact with a cam (2), a slave piston (5) that acts on a gas exchange valve (4) and a pressure chamber (6) of variable volume that is positioned between the master and the slave pistons (3, 5). The chamber is intersected by a path (7) for supplying and selectively draining hydraulic fluid, said path being subjected to the action of a switching element (8), such as an electromagnet for influencing the pressure of the hydraulic fluid. A secondary path (9) branches from the path (7) to a pressure accumulator (10), the latter (10) comprising a piston (12) in the direction of flow of the path (7) that is subjected to the action of a spring element (11). The invention is characterised in that the path (7) is connected to a hydraulic fluid reservoir (13), which consists of a pot-type element (14) comprising a non-return valve (16) on its base (15) that faces the path (7). Said valve opens in the direction of the path (7) and closes in the direction of flow to an inner chamber (18) that is surrounded by the wall (17) of the element (14). An intentional passage (21) in the form of a leakage gap is configured starting from one side of the path (19) of the element (14) and running radially between the wall (17) and a guide (20) for said element (14), said passage supplying the hydraulic fluid from the path (7) to the inner chamber (18), where it accumulates. This configuration permits the provision of a valve gear (1), which prevents the intake of air into the pressure chamber (6) of the valve gear, during the operation of the internal combustion engine.

IPC 1-7

F01L 9/02

IPC 8 full level

F01L 9/12 (2021.01); F01L 9/14 (2021.01)

CPC (source: EP)

F01L 9/12 (2021.01); F01L 9/14 (2021.01); F01L 2001/34446 (2013.01)

Citation (search report)

See references of WO 03102383A1

Cited by

GB2562268A

Designated contracting state (EPC)

DE FR GB IT SE

DOCDB simple family (publication)

WO 03102383 A1 20031211; AU 2003245877 A1 20031219; DE 10224038 A1 20031211; DE 50309325 D1 20080417; EP 1509685 A1 20050302; EP 1509685 B1 20080305

DOCDB simple family (application)

EP 0304294 W 20030425; AU 2003245877 A 20030425; DE 10224038 A 20020531; DE 50309325 T 20030425; EP 03737957 A 20030425