

Title (en)

Method and device for switching a fluid flow

Title (de)

Verfahren und Vorrichtung zur Flutumschaltung

Title (fr)

Procédé et dispositif pour commuter un flux

Publication

EP 1510699 A3 20050720 (DE)

Application

EP 04018691 A 20040806

Priority

DE 10338881 A 20030823

Abstract (en)

[origin: EP1510699A2] The method involves advancing two sliders (2) independently of each other during a time interval of a switchover from a pump (40) into a hydraulic line or a reservoir using a three-way valve (8). An axial motion of the sliders is initiated in the valve by a rise and drop of a pilot pressure in the valve. A quantity of oil in the sliders is directed in a predetermined direction during switchover. An independent claim is also included for a fluid device.

IPC 1-7

F15B 13/04

IPC 8 full level

F16K 31/363 (2006.01); **F15B 13/04** (2006.01); **F16K 11/07** (2006.01); **F16K 31/72** (2006.01)

CPC (source: EP US)

F15B 13/0403 (2013.01 - EP US); **Y10T 137/86582** (2015.04 - EP US); **Y10T 137/8663** (2015.04 - EP US)

Citation (search report)

- [X] EP 1279870 A1 20030129 - BOSCH REXROTH AG [DE]
- [DA] DE 3629479 A1 19870716 - BARMAG BARMER MASCHF [DE]
- [A] DE 3723672 A1 19890126 - WESSEL HYDRAULIK [DE]

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

EP 1510699 A2 20050302; EP 1510699 A3 20050720; EP 1510699 B1 20080305; AT E388331 T1 20080315; DE 102004038193 A1 20050317;
DE 502004006385 D1 20080417; JP 2005069482 A 20050317; US 2005039803 A1 20050224; US 7458396 B2 20081202

DOCDB simple family (application)

EP 04018691 A 20040806; AT 04018691 T 20040806; DE 102004038193 A 20040806; DE 502004006385 T 20040806;
JP 2004240676 A 20040820; US 91994104 A 20040817