

Title (en)

HIGH STRENGTH COLD ROLLED STEEL PLATE AND METHOD FOR PRODUCTION THEREOF

Title (de)

HOCHFESTE KALTGEWALZTE STAHLPLATTE UND HERSTELLUNGSVERFAHREN DAFÜR

Title (fr)

TOLE D'ACIER LAMINE A FROID A HAUTE RESISTANCE ET PROCEDE DE FABRICATION

Publication

EP 1514951 B1 20101124 (EN)

Application

EP 03736017 A 20030604

Priority

- JP 0307062 W 20030604
- JP 2002173668 A 20020614
- JP 2002173669 A 20020614

Abstract (en)

[origin: EP1514951A1] The present invention provides a high strength cold-rolled steel sheet, consisting essentially of, by mass%, 0.04 to 0.10% C, 0.5 to 1.5% Si, 1.8 to 3% Mn, 0.02% or less P, 0.01% or less S, 0.01 to 0.1% Sol. Al, 0.005% or less N, and the balance being iron and inevitable impurities, and having a structure which substantially comprises ferrite phase and martensite phase. Since the high strength cold-rolled steel sheet of the invention has ductility in which an elongation is 18% or more, excellent stretch-flangeability in which a hole-expanding ratio is 60% or more and a tensile strength of 780 MPa or more, it is favorable for use in a structural member of automobile.

IPC 8 full level

C22C 38/00 (2006.01); **C21D 9/46** (2006.01); **C22C 38/02** (2006.01); **C22C 38/04** (2006.01); **C22C 38/06** (2006.01); **C22C 38/38** (2006.01);
C21D 8/02 (2006.01)

CPC (source: EP US)

C22C 38/02 (2013.01 - EP US); **C22C 38/04** (2013.01 - EP US); **C22C 38/06** (2013.01 - EP US); **C21D 8/0236** (2013.01 - EP US);
C21D 2211/005 (2013.01 - EP US); **C21D 2211/008** (2013.01 - EP US)

Cited by

EP2194153A3; EP2000554A4; EP2157203A1; EP2785889A4; US8298356B2; US8465600B2; US8128762B2

Designated contracting state (EPC)

DE SE

DOCDB simple family (publication)

EP 1514951 A1 20050316; EP 1514951 A4 20060510; EP 1514951 B1 20101124; DE 60335106 D1 20110105; EP 2017363 A2 20090121;
EP 2017363 A3 20090805; US 2004238082 A1 20041202; WO 03106723 A1 20031224

DOCDB simple family (application)

EP 03736017 A 20030604; DE 60335106 T 20030604; EP 08159197 A 20030604; JP 0307062 W 20030604; US 48578004 A 20040329