

Title (en)  
Lock cylinder with electromechanical control

Title (de)  
Schliesszylinder mit elektromechanischer Steuerung

Title (fr)  
Cylindre de serrure à contrôle électromécanique

Publication  
**EP 1518979 B1 20070221 (FR)**

Application  
**EP 04292307 A 20040927**

Priority  
FR 0311223 A 20030925

Abstract (en)  
[origin: EP1518979A1] The cylinder/lock has a ring (4) pivotably and coaxially mounted around a rotor under the control of an electric motor (2). The ring has a groove (5) inclined with respect to rotation axis of the ring and cooperates with a projection (8) of a flake (1). The ring is integrated to an end of a coil spring that drives the ring when the motor does not control the ring so as to drive the flake to lock the rotor.

IPC 8 full level  
**E05B 47/06** (2006.01); **E05B 29/00** (2006.01); **E05B 47/00** (2006.01)

CPC (source: EP)  
**E05B 47/0642** (2013.01); **E05B 47/0012** (2013.01); **E05B 2047/0025** (2013.01)

Cited by  
CN109538019A; CN110130735A; EP4019718A4

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)  
**EP 1518979 A1 20050330; EP 1518979 B1 20070221**; AT E354712 T1 20070315; DE 602004004851 D1 20070405;  
DE 602004004851 T2 20071115; FR 2860259 A1 20050401; FR 2860259 B1 20070223; PL 1518979 T3 20070831; SI 1518979 T1 20070831

DOCDB simple family (application)  
**EP 04292307 A 20040927**; AT 04292307 T 20040927; DE 602004004851 T 20040927; FR 0311223 A 20030925; PL 04292307 T 20040927;  
SI 200430289 T 20040927