

Title (en)

Five axis machine tool with continuous grinding wheel dressing device

Title (de)

Fünfachsigte Werkzeugmaschine mit fortlaufender Schleifscheibenabrichtvorrichtung

Title (fr)

Machine-outil à 5 axes d'usinage avec système de taillage de meule en continu

Publication

EP 1522378 B1 20091209 (FR)

Application

EP 04292338 A 20041001

Priority

FR 0311710 A 20031007

Abstract (en)

[origin: FR2860448A1] The tool has a work-holder (4) rotated around a vertical axis (A1) by a driving unit arranged in a bed (6) rotated along a horizontal axis (A2). A machining system has a grinding wheel (2) and a barrel structure (100) moving along three axes (X-Z). The structure with a main spindle (21) rotating the wheel is coupled to a rotating device (12) having a spindle (11) coupled to a knurl (1) moving around a rotation axis of the wheel.

IPC 8 full level

B23Q 1/62 (2006.01); **B24B 41/00** (2006.01); **B24B 53/053** (2006.01)

CPC (source: EP US)

B24B 41/00 (2013.01 - EP US); **B24B 53/053** (2013.01 - EP US)

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

EP 1522378 A1 20050413; **EP 1522378 B1 20091209**; AT E451198 T1 20091215; DE 602004024487 D1 20100121; FR 2860448 A1 20050408; FR 2860448 B1 20060106; US 2005118928 A1 20050602; US 7195543 B2 20070327

DOCDB simple family (application)

EP 04292338 A 20041001; AT 04292338 T 20041001; DE 602004024487 T 20041001; FR 0311710 A 20031007; US 95959304 A 20041006