

Title (en)
Fall arrest device with blocking catch

Title (de)
Fallschutzgerät mit sperrender Zuhaltung

Title (fr)
Dispositif antichute à galet bloqueur

Publication
EP 1525903 B1 20060823 (FR)

Application
EP 04354024 A 20040623

Priority
FR 0312247 A 20031020

Abstract (en)
[origin: EP1525903A1] A centrifugal coupling is arranged between a drive member of a locking roller and a support arm to occupy disengaged or engaged position. The centrifugal coupling has a flyweight movable along the arm of drive member against a tension spring, and a connecting interface engaged inside the cylindrical rim of support arm to transmit elastic force of spring to flyweight. The device (10) has a body (16) having a movable security system (18) with the support arm articulated on a first spindle (24) of the body. The locking roller, consists of a cylindrical wheel, is mounted to rotate freely on a second spindle attached to the support arm.

IPC 8 full level
A62B 1/14 (2006.01); **A62B 35/00** (2006.01); **A47L 3/04** (2006.01); **A62B 1/10** (2006.01); **A62B 1/16** (2006.01)

CPC (source: EP US)
A62B 1/10 (2013.01 - EP US); **A62B 1/14** (2013.01 - EP US)

Cited by
EP2754466A1; CN101850161A; EP2974775A1; FR3023726A1; FR2903318A1; FR3000900A1; FR3095952A1; US9533192B2; DE102021102673A1; US9498660B2; EP2754465A1; US9192792B2

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)
EP 1525903 A1 20050427; **EP 1525903 B1 20060823**; AT E337051 T1 20060915; DE 602004002060 D1 20061005; DE 602004002060 T2 20070308; ES 2271818 T3 20070416; FR 2860982 A1 20050422; FR 2860982 B1 20060120; JP 2005125077 A 20050519; JP 4566643 B2 20101020; US 2005082115 A1 20050421; US 7137481 B2 20061121

DOCDB simple family (application)
EP 04354024 A 20040623; AT 04354024 T 20040623; DE 602004002060 T 20040623; ES 04354024 T 20040623; FR 0312247 A 20031020; JP 2004214485 A 20040722; US 88056704 A 20040701