

Title (en)

TOOL HOLDING FIXTURE FOR A MACHINE TOOL

Title (de)

WERKZEUGAUFNAHME FÜR EINE WERKZEUGMASCHINE

Title (fr)

RACCORDEMENT D'OUTIL POUR MACHINE-OUTIL

Publication

EP 1526950 A1 20050504 (DE)

Application

EP 03763580 A 20030627

Priority

- DE 0302142 W 20030627
- DE 10230991 A 20020710

Abstract (en)

[origin: WO2004007149A1] The invention relates to a tool holding fixture for a machine tool, particularly for a hammer drill, provided with a locating opening (12) for holding a tool shank (14) and with a percussive pin (16). During operation, the tool shank (14) and/or the percussive pin (16) have/has an operating position located between an idle position and a percussive position. The inventive tool holding fixture also comprises a lubricant opening (56), which is stationary relative to the percussive pin (16) and which is provided for supplying lubricant, and comprises a lubricant valve (16, 56) having a variable valve control for dosing the lubricant. According to the invention, the valve control of the lubricant valve (16, 56) is dependent on the operating position of the percussive pin (16) and/or of the tool shank (14) between the idle position and the percussive position.

IPC 1-7

B25D 17/08; **B25D 17/26**

IPC 8 full level

B23B 31/02 (2006.01); **B23B 45/16** (2006.01); **B25D 9/00** (2006.01); **B25D 17/08** (2006.01); **B25D 17/26** (2006.01)

CPC (source: EP US)

B25D 17/088 (2013.01 - EP US); **B25D 17/26** (2013.01 - EP US); **B25D 2217/0042** (2013.01 - EP US); **B25D 2250/191** (2013.01 - EP US)

Citation (search report)

See references of WO 2004007149A1

Designated contracting state (EPC)

CH DE GB LI

DOCDB simple family (publication)

WO 2004007149 A1 20040122; CN 100374253 C 20080312; CN 1665647 A 20050907; DE 10230991 A1 20040212; EP 1526950 A1 20050504; JP 2005532185 A 20051027; US 2005224243 A1 20051013

DOCDB simple family (application)

DE 0302142 W 20030627; CN 03816242 A 20030627; DE 10230991 A 20020710; EP 03763580 A 20030627; JP 2004520298 A 20030627; US 51393404 A 20041110