

Title (en)
ATTENUATION OR TERMINATION ELEMENT HAVING A COAXIAL STRUCTURE FOR HIGH-FREQUENCY ELECTROMAGNETIC WAVES

Title (de)
DÄMPFUNGS- ODER ABSCHLUSSELEMENT IN KOAXIALBAUWEISE FÜR HOCHFREQUENTE ELEKTROMAGNETISCHE WELLEN

Title (fr)
ELEMENT D'ATTENUATION OU DE TERMINAISON A STRUCTURE COAXIALE POUR ONDES ELECTROMAGNETIQUES HAUTE FREQUENCE

Publication
EP 1535364 A1 20050601 (DE)

Application
EP 03793557 A 20030829

Priority
• CH 0300590 W 20030829
• CH 15072002 A 20020904

Abstract (en)
[origin: WO2004023596A1] The invention relates to an attenuation or termination element comprising at least one resistance part (3, 3') which is mounted in an outer conductor (2) and has at least one connection to an inner conductor part (7, 8). Said resistance part (3, 3') is produced from at least two separately produced plate-shaped parts (4, 5; 4', 5') which are preferably provided with a central slit (12, 13) enabling them to be fitted together. Said attenuation or termination element (1, 1') can be economically produced and has high heat dissipation.

IPC 1-7
H01P 1/22; **H01P 1/26**

IPC 8 full level
H01P 1/22 (2006.01); **H01P 1/26** (2006.01)

CPC (source: EP US)
H01P 1/225 (2013.01 - EP US); **H01P 1/266** (2013.01 - EP US)

Citation (search report)
See references of WO 2004023596A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT RO SE SI SK TR

DOCDB simple family (publication)
WO 2004023596 A1 20040318; AT E390724 T1 20080415; AU 2003254692 A1 20040329; DE 50309484 D1 20080508;
EP 1535364 A1 20050601; EP 1535364 B1 20080326; HK 1075134 A1 20051202; US 2006097817 A1 20060511; US 7212079 B2 20070501

DOCDB simple family (application)
CH 0300590 W 20030829; AT 03793557 T 20030829; AU 2003254692 A 20030829; DE 50309484 T 20030829; EP 03793557 A 20030829;
HK 05107323 A 20050822; US 52629205 A 20050301