

Title (en)

Method and means for correcting the positional deviation of a printing product

Title (de)

Verfahren und Vorrichtung zur Korrektur der Lageabweichung eines Transportgutes

Title (fr)

Procédé et dispositif pour corriger la déviation de la position d'un produit à imprimer

Publication

EP 1543963 B1 20121212 (DE)

Application

EP 04024237 A 20041012

Priority

DE 10360168 A 20031220

Abstract (en)

[origin: EP1543963A1] The method involves establishing the deviation from an ideal position and selecting a suitable correction profile from a number of selectable profiles. These selectable profiles (P1,P2,P3) can be stored in the control of the transport mechanism (10). Independent claim describes a correction device where a device (21) is provided for storing a number of selectable correction profiles. These can be in the form of support point tables.

IPC 8 full level

B41F 13/12 (2006.01); **B65H 5/06** (2006.01)

CPC (source: EP US)

B41F 13/12 (2013.01 - EP US); **B41P 2213/91** (2013.01 - EP US)

Citation (examination)

- DE 4436034 A1 19960411 - ROLAND MAN DRUCKMASCH [DE]
- DE 4444755 A1 19950803 - HEIDELBERGER DRUCKMASCH AG [DE]

Cited by

EP1745925B2

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

EP 1543963 A1 20050622; EP 1543963 B1 20121212; DE 10360168 A1 20050721; JP 2005179066 A 20050707; US 2005132918 A1 20050623; US 7117795 B2 20061010

DOCDB simple family (application)

EP 04024237 A 20041012; DE 10360168 A 20031220; JP 2004368444 A 20041220; US 1310704 A 20041215