

Title (en)

A FASTENER AND A METHOD FOR ITS MANUFACTURE

Title (de)

BEFESTIGUNGSVORRICHTUNG UND VERFAHREN ZU IHRER HERSTELLUNG

Title (fr)

FERMETURE A GLISSIERE ECLAIR ET SON PROCEDE DE FABRICATION

Publication

**EP 1545257 A1 20050629 (EN)**

Application

**EP 03782175 A 20030912**

Priority

- EP 0310177 W 20030912
- IT TO20020797 A 20020913

Abstract (en)

[origin: WO2004023918A1] A fastener (F) comprising two tapes (1, 2) , made of a flexible fabric. Around a respective longitudinal edge (1a, 2a) of each of said tapes (1, 2) a respective plurality of separate coupling members (3; 3a, 3b) adapted to be engaged with and disengaged from those of the other tape (2, 1) is fixed. The tapes (1, 2) are made of a knitted fabric including a plurality of longitudinal chain threads (C1, C2, ...) interlaced by tricot or weft threads (A1, B1; A2, B2; ...) extending along respective sinuous paths so as to form a corresponding plurality of longitudinal stitch wales (W12, W23, W34, ...). An essentially inextensible anchoring cord (AC) extends and is firmly retained through the first stitch wale (W12) of each tape (1, 2) adjacent the said edge (1a, 2a). The coupling members (3; 3a, 3b) of each tape (1, 2) grips the said anchoring cord (AC).

IPC 1-7

**A44B 19/34**

IPC 8 full level

**A44B 19/34** (2006.01)

CPC (source: EP)

**A44B 19/343** (2013.01)

Citation (search report)

See references of WO 2004023918A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT RO SE SI SK TR

DOCDB simple family (publication)

**WO 2004023918 A1 20040325**; AT E406122 T1 20080915; AU 2003289848 A1 20040430; DE 60323247 D1 20081009; EP 1545257 A1 20050629; EP 1545257 B1 20080827; EP 1545257 B8 20081022; IT TO20020797 A1 20040314

DOCDB simple family (application)

**EP 0310177 W 20030912**; AT 03782175 T 20030912; AU 2003289848 A 20030912; DE 60323247 T 20030912; EP 03782175 A 20030912; IT TO20020797 A 20020913