

Title (en)
Continuous mode ballast with pulsed operation

Title (de)
Vorschaltgerät mit gepulster Steuerung

Title (fr)
Ballast avec mode pulsé

Publication
EP 1551208 A2 20050706 (EN)

Application
EP 04258060 A 20041222

Priority
US 75115504 A 20040102

Abstract (en)
In accordance with one aspect of the present application, a continuous mode electronic ballast (10) for operating an HID lamp (28) includes an inverter circuit (12) configured to generate a control signal. A resonant circuit (14) is operationally coupled to the inverter circuit and to the lamp and configured to generate resonant voltage in response to receiving the control signal generated by the inverter circuit. A clamping circuit (16) is operationally coupled to the resonant circuit to limit the voltage across the resonant circuit to protect components of the ballast. A multiplier circuit (82) is operationally coupled to the resonant circuit to boost the voltage clamped by the clamping circuit to a value sufficient to permit starting of the lamp. The clamping circuit and the multiplier circuit cooperate to facilitate a continuous starting of the lamp.

IPC 1-7
H05B 41/288; **H05B 41/292**

IPC 8 full level
H05B 41/288 (2006.01); **H05B 41/292** (2006.01)

CPC (source: EP US)
H05B 41/2881 (2013.01 - EP US); **H05B 41/2925** (2013.01 - EP US); **Y02B 20/00** (2013.01 - EP US)

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)
EP 1551208 A2 20050706; **EP 1551208 A3 20060510**; CN 1638590 A 20050713; JP 2005198494 A 20050721; US 2005146287 A1 20050707; US 6952085 B2 20051004

DOCDB simple family (application)
EP 04258060 A 20041222; CN 200410104479 A 20041231; JP 2004380339 A 20041228; US 75115504 A 20040102