

Title (en)

CUSHIONING MEMBER AND METHOD OF MANUFACTURING THE SAME

Title (de)

POLSTERGLIED UND HERSTELLUNGSVERFAHREN DAFÜR

Title (fr)

ELEMENT AMORTISSEUR ET PROCEDE DE FABRICATION DE CELUI-CI

Publication

EP 1556627 A2 20050727 (EN)

Application

EP 03781465 A 20031030

Priority

- JP 2002318046 A 20021031
- US 0334393 W 20031030

Abstract (en)

[origin: WO2004042248A2] A cushioning member is located between each support frame and the corresponding side of the shutter. The cushioning member includes a pair of belt-shaped base members and pile yarns bridging between the base members. Some of the pile yarns are cut at intermediate portion between the base members, which forms opposing first and second cut pile yarns with a cut in between. One of the base members is attached to each support frame, and the other base member contacts the shutter. The cut permits the cushioning member to flexibly respond to movements of the shutter and satisfactorily exerts a cushioning function to suppress swaying of the shutter.

IPC 1-7

F16F 1/36

IPC 8 full level

E06B 7/22 (2006.01); **E06B 7/23** (2006.01); **E06B 9/17** (2006.01); **E06B 9/58** (2006.01); **F16F 7/00** (2006.01); **F16F 15/08** (2006.01)

CPC (source: EP)

E06B 7/22 (2013.01); **E06B 9/17076** (2013.01); **E06B 9/582** (2013.01); **F16F 7/00** (2013.01)

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT RO SE SI SK TR

DOCDB simple family (publication)

WO 2004042248 A2 20040521; WO 2004042248 A3 20050506; AU 2003288973 A1 20040607; CA 2504253 A1 20040521;
EP 1556627 A2 20050727; EP 1556627 A4 20070124; JP 2004150182 A 20040527; JP 2006515252 A 20060525; JP 4242837 B2 20090325;
MX PA05004454 A 20051123

DOCDB simple family (application)

US 0334393 W 20031030; AU 2003288973 A 20031030; CA 2504253 A 20031030; EP 03781465 A 20031030; JP 2002318046 A 20021031;
JP 2004550220 A 20031030; MX PA05004454 A 20031030