

Title (en)
METHOD FOR CLEANING THE SCREEN STENCIL OF A SILK-SCREEN PRINTING DEVICE AND SILK-SCREEN PRINTING MACHINE FOR SAID METHOD

Title (de)
VERFAHREN ZUR REINIGUNG DER SIEBSCHABLONE EINER SIEBDRUCKEINRICHTUNG UND SIEBDRUCKMASCHINE ZUR DURCHFÜHRUNG DES VERFAHRENS

Title (fr)
PROCEDE DE NETTOYAGE DE L'ECRAN D'UNE INSTALLATION DE SERIGRAPHIE ET MACHINE DE SERIGRAPHIE PERMETTANT DE METTRE EN OEUVRE CE PROCEDE

Publication
EP 1565314 A1 20050824 (DE)

Application
EP 03772227 A 20031016

Priority
• DE 10256326 A 20021127
• EP 0311475 W 20031016

Abstract (en)
[origin: US7434510B2] A cleaning method for the screen stencil of a silk-screen printing machine. According to the method, prior to an intermediate printing process designed to clean the screen stencil, the underside of the stencil is wetted with a cleaning agent that dissolves dye. An intermediate printing device includes an intermediate printing roll that can be displaced back and forth. A rotating roll that is immersed in a cleaning bath is situated at the front end of the intermediate printing roll. The rotating roll can be brought into contact with the underside of the screen stencil prior to the intermediate printing process by means of a pivoting device.

IPC 1-7
B41F 11/00

IPC 8 full level
B41F 35/00 (2006.01)

CPC (source: EP US)
B41F 35/005 (2013.01 - EP US)

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT RO SE SI SK TR

DOCDB simple family (publication)
WO 2004048098 A1 20040610; WO 2004048098 A8 20041118; AT E534516 T1 20111215; AU 2003280385 A1 20040618; AU 2003280385 A8 20040618; DE 10256326 A1 20040617; EP 1565314 A1 20050824; EP 1565314 B1 20111123; PL 377001 A1 20060123; US 2006180037 A1 20060817; US 7434510 B2 20081014

DOCDB simple family (application)
EP 0311475 W 20031016; AT 03772227 T 20031016; AU 2003280385 A 20031016; DE 10256326 A 20021127; EP 03772227 A 20031016; PL 37700103 A 20031016; US 53679505 A 20051230