

Title (en)

USE OF A STEEL ALLOY AS A MATERIAL FOR PRODUCING THICK-WALLED TUBULAR PARTS FOR MOTOR VEHICLES

Title (de)

VERWENDUNG EINER STAHLLEGIERUNG ALS WERKSTOFF ZUR HERSTELLUNG VON DICKWANDIGEN ROHRBAUTEILEN FÜR KRAFTFAHRZEUGE

Title (fr)

UTILISATION D'UN ALLIAGE D'ACIER COMME MATIERE PREMIERE POUR LA PRODUCTION DE COMPOSANTS TUBULAIRES A PAROI EPAISSE DESTINES A DES VEHICULES AUTOMOBILES

Publication

EP 1565588 A1 20050824 (DE)

Application

EP 03767465 A 20031126

Priority

- DE 0303925 W 20031126
- DE 10255264 A 20021127

Abstract (en)

[origin: WO2004048628A1] The invention relates to a steel alloy that consists, in percentages by mass, of: 0.09 0.13 % carbon (C); 0.15 0.30 % silicon (Si); 1.10 1.60 % manganese (Mn); a maximum of 0.015 % phosphorous (P); a maximum of 0.011 % sulfur (S); 1.00 1.60 % chromium (Cr); 0.30 0.60 % molybdenum (Mo); 0.020 0.050 % aluminum (Al); 0.12 0.25 % vanadium (V), and; as the remainder, iron as well as impurities that result during smelting. This steel alloy is used as a material for tubes, which are air-hardened or both air-hardened and tempered, for producing thick-walled tubular parts for motor vehicles.

IPC 1-7

C22C 38/18; **C22C 38/22**; **C22C 38/24**; **C21D 9/08**; **C21D 1/02**; **C22C 38/38**

IPC 8 full level

C22C 38/22 (2006.01); **C22C 38/24** (2006.01); **C22C 38/38** (2006.01); **C21D 1/02** (2006.01); **C21D 9/08** (2006.01)

CPC (source: EP)

C22C 38/22 (2013.01); **C22C 38/24** (2013.01); **C22C 38/38** (2013.01); **C21D 1/02** (2013.01); **C21D 9/085** (2013.01)

Citation (search report)

See references of WO 2004048628A1

Cited by

EP1881083A1

Designated contracting state (EPC)

DE

DOCDB simple family (publication)

WO 2004048628 A1 20040610; AU 2003291954 A1 20040618; DE 10255264 A1 20040617; DE 50302755 D1 20060511; EP 1565588 A1 20050824; EP 1565588 B1 20060322

DOCDB simple family (application)

DE 0303925 W 20031126; AU 2003291954 A 20031126; DE 10255264 A 20021127; DE 50302755 T 20031126; EP 03767465 A 20031126