

Title (en)
STANDARD MICRO-COMPONENT FOR CALIBRATING OR STANDARDIZING FLUORESCENCE MEASURING INSTRUMENTS AND BIOCHIP COMPRISING SAME

Title (de)
STANDARDMIKROKOMPONENTE ZUR KALIBRIERUNG ODER STANDARDISIERUNG VON FLUORESZENZMESSINSTRUMENTEN UND BIOCHIP DAMIT

Title (fr)
MICRO-COMPOSANT ETALON POUR LE CALIBRAGE OU L'ETALONNAGE D'EQUIPEMENTS DE MESURE DE FLUORESCENCE ET BIOPUCE LE COMPORTANT

Publication
EP 1573304 A1 20050914 (FR)

Application
EP 03815387 A 20031210

Priority
• FR 0303656 W 20031210
• FR 0216012 A 20021217

Abstract (en)
[origin: FR2848670A1] The standardised micro-component (4) consists of a substrate (1) with at least one thin deposited layer (2) containing components with a first level of fluorescence, and at least one isolated zone (2a) with a second, lower level of fluorescence. The deposited layer also has at least one aperture (3) in it defining a third level of fluorescence which is lower than the first two and corresponds to the fluorescence level of the substrate, being at least ten times and up to 100 times lower than the first and second levels. The thin deposited layer is a fluorescent material such as a light-sensitive resin, and the substrate is of a material selected from silicium, synthetic silica, quartz, plastic and glass.

IPC 1-7
G01N 21/64

IPC 8 full level
G01N 21/27 (2006.01); **G01N 21/64** (2006.01)

CPC (source: EP US)
G01N 21/278 (2013.01 - EP US); **G01N 21/645** (2013.01 - EP US)

Citation (search report)
See references of WO 2004065946A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT RO SE SI SK TR

DOCDB simple family (publication)
FR 2848670 A1 20040618; **FR 2848670 B1 20050610**; AU 2003296803 A1 20040813; AU 2003296803 A8 20040813; EP 1573304 A1 20050914; JP 2006510916 A 20060330; US 2006060931 A1 20060323; WO 2004065946 A1 20040805

DOCDB simple family (application)
FR 0216012 A 20021217; AU 2003296803 A 20031210; EP 03815387 A 20031210; FR 0303656 W 20031210; JP 2004566985 A 20031210; US 53886605 A 20050614