

Title (en)
Dry wall

Title (de)
Trockenbauwand

Title (fr)
Mur en construction sèche

Publication
EP 1574632 A2 20050914 (DE)

Application
EP 05001386 A 20050125

Priority
DE 202004003535 U 20040308

Abstract (en)
The C-stands (2) and plasterboard panels (3) extending between the floor (B) and the bottom of the high window glazing (O) are mounted in at least one rectangular frame (1) assembled from wooden profiles (1a, 1b). The frame is secured to the floor and located in between the plasterboard panels covering both sides of the C-stands. The cavities inside the C-stands are filled with mineral wool.

Abstract (de)
Die Erfindung betrifft eine Trockenbauwand mit einer im Oberlichtbereich angeordneten Verglasung und mit C-Ständern aus Stahlblech, die auf beiden Seiten mit Gipskartonplatten oder dergleichen beplankt und im Innern mit Mineralwolle ausgefüllt sind, wobei die lediglich zwischen dem Boden (B) und der Unterkante der Oberlichtverglasung (O) verlaufenden C-Ständer mit ihrer Beplankung durch mindestens einen rechteckigen Rahmen (1) aus Holzprofilen (1a, 1b) gehalten sind, der am Boden (B) befestigt ist und innerhalb der Beplankung verläuft. <IMAGE>

IPC 1-7
E04B 2/74

IPC 8 full level
E04B 2/74 (2006.01)

CPC (source: EP)
E04B 2/7455 (2013.01); **E04B 2/7457** (2013.01)

Cited by
CN114991356A; DE202014103095U1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)
EP 1574632 A2 20050914; **EP 1574632 A3 20060712**; **EP 1574632 B1 20080827**; AT E406487 T1 20080915; DE 202004003535 U1 20040513; DE 502005005163 D1 20081009

DOCDB simple family (application)
EP 05001386 A 20050125; AT 05001386 T 20050125; DE 202004003535 U 20040308; DE 502005005163 T 20050125