

Title (en)
ANTI-FOULING VARNISH, METHOD FOR APPLICATION OF SAID VARNISH TO A SILICONE SUPPORT AND SUPPORT TREATED THUS

Title (de)
ANTIFOULINGLACK, VERFAHREN ZUM AUFBRINGEN DES LACKS AUF EINENSILIKONTRÄGER UND SO BEHANDELTEN TRÄGER

Title (fr)
VERNIS ANTI-SALISSURES, PROCÉDÉ D'APPLICATION DE CE VERNIS SUR UN SUPPORT SILICONE ET SUPPORT AINSI TRAITÉ.

Publication
EP 1576045 A1 20050921 (FR)

Application
EP 03815557 A 20031208

Priority
• FR 0303618 W 20031208
• FR 0216713 A 20021226

Abstract (en)
[origin: FR2849446A1] A cationically polymerizable and crosslinkable silylated lacquer (I) comprises (by weight) at least 80% base compound containing polymerizable/crosslinkable groups, at least one of which is alkenyl ether, epoxy or oxetane; 0.1-10% cationic initiator having onium salt cation and borate anion; 0-10% polyorganosiloxane containing alkenyl group(s) and/or epoxy group(s); 0-10% silyl compound containing epoxy group(s); and 0-10% silyl compound containing alkenyl group(s) and/or epoxy, alkenyl ether or oxetane group(s). A cationically polymerizable and crosslinkable silylated lacquer (I), specifically having antisoiling properties, comprises (by weight): (a) at least 80% base compound(s) containing at least two polymerizable/crosslinkable groups, at least one of which is alkenyl ether, epoxy or oxetane; (b) 0.1-10% cationic initiator(s) having an onium salt cation of formula ((R1)n-A-(R2)m)+ and a borate anion of formula (BXaRb)-; (c) 0-10% polyorganosiloxane(s) (POS) containing at least one alkenyl group (preferably (meth)acrylic or its salt) and/or at least one epoxy group; (d) 0-10% silyl compound(s) containing at least one epoxy group; (e) 0-10% silyl compound(s) containing at least one alkenyl group (preferably (meth)acrylic or its salt) and/or at least one epoxy, alkenyl ether or oxetane group (provided that the POS and epoxy-silyl compound must be present if this compound is absent; and this compound must be present if the POS and epoxy-silyl compound are absent); (f) 0-10% ultrafine filler(s); (g) 0-10% thickener(s); and (h) 0-10% functional additive(s). A = element of groups 15-17 (e.g. I, S, Se, P or N), having valency v; R1 = 6-20C carbocyclic or heterocyclic aryl (optionally containing N or S as heteroatom), optionally substituted by 1-25C alkoxy, -1-25C alkyl, NO2, Cl, Br, CN, COOH, ester group or SH; R2 = as R1, 1-20C alkyl or 2-20C alkenyl (all optionally substituted as for R1); n = 1 to (v+1); m = 0 to (v-1); a = 0-3; b = 1-4, provided that (a+b) = 4; X = halo (F or Cl) or OH, provided that a = 0-2 if X = OH; and R = (i) phenyl substituted by at least one electron-attracting group (e.g. OCF3, CF3, NO2 or CN) and/or at least two halo (preferably F), in which case the cation is an onium compound of a group 15-17 element, (ii) phenyl substituted by at least one electron-attracting group, especially halo (preferably F), OCF3, CF3, NO2 or CN, in which case the cation is an organometallic complex of a group 4-10 element or (iii) aryl containing at least two aromatic rings (e.g. biphenyl or naphthyl), optionally substituted by at least one electron-attracting group, especially halo (preferably F), OCF3, CF3, NO2 or CN. Independent claims are also included for: (1) a method for lacquering architectural textiles or other substrates, involving applying (I) to the silicone surface of a substrate formed at least partially from silicone (preferably silicone elastomer); (2) composites (other than architectural textiles), obtained by the above method and comprising either (a) a (preferably flexible) support (specifically a textile, non-woven or polymer film), optionally a coating (comprising at least one layer of silicone elastomer and at least one other (co)polymer) on at least one face of the support and at least one layer of the lacquer (I) or (b) a solid supporting mass (optionally of silicone and/or at least partially coated with silicone, specifically silicone elastomer) at least one layer of the lacquer (I); (3) composite architectural textiles, obtained by the above method and comprising a (preferably flexible) support (specifically a textile, non-woven or polymer film), optionally a coating (comprising at least one layer of silicone elastomer and at least one other (co)polymer) on at least one face of the support and at least one layer of the lacquer (I); and (4) manufactured articles comprising the composite architectural textiles or other composites.

IPC 1-7
C08K 5/55; C08J 7/04; C09D 183/06; C08G 59/24; C08G 59/30; C09D 163/00

IPC 8 full level
C08G 59/30 (2006.01); **C08K 5/151** (2006.01); **C08K 5/5435** (2006.01); **C08K 5/55** (2006.01); **C09D 163/00** (2006.01); **C09D 183/06** (2006.01); **C09D 183/07** (2006.01)

CPC (source: EP US)
C08G 59/306 (2013.01 - EP US); **C08K 5/151** (2013.01 - EP US); **C08K 5/5435** (2013.01 - EP US); **C08K 5/55** (2013.01 - EP US); **C09D 163/00** (2013.01 - EP US); **C09D 183/06** (2013.01 - EP US); **Y10T 428/2962** (2015.01 - EP US); **Y10T 428/31663** (2015.04 - EP US); **Y10T 442/2525** (2015.04 - EP US)

Citation (search report)
See references of WO 2004067620A1

Cited by
WO2011134686A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT RO SE SI SK TR

DOCDB simple family (publication)
FR 2849446 A1 20040702; FR 2849446 B1 20060728; AU 2003296776 A1 20040823; CN 100445326 C 20081224; CN 1742048 A 20060301; EP 1576045 A1 20050921; JP 2006512468 A 20060413; JP 4272167 B2 20090603; US 2006039889 A1 20060223; US 2009186224 A1 20090723; US 7790785 B2 20100907; US 7868056 B2 20110111; WO 2004067620 A1 20040812

DOCDB simple family (application)
FR 0216713 A 20021226; AU 2003296776 A 20031208; CN 200380109163 A 20031208; EP 03815557 A 20031208; FR 0303618 W 20031208; JP 2004567356 A 20031208; US 16638005 A 20050627; US 31884309 A 20090109