

Title (en)

Key

Title (de)

Schlüssel

Title (fr)

Clé

Publication

EP 1577469 A3 20060419 (DE)

Application

EP 05101380 A 20050223

Priority

DE 102004013522 A 20040319

Abstract (en)

[origin: EP1577469A2] Key (4) for a lock cylinder having a series of pin tumblers (7, 7') comprises a shaft (11), a series of lock recesses (12) arranged a certain distance (a) apart in the shaft, and a key tip (15) arranged on its free end and having an insertion bevel (16). The insertion bevel is located outside the arrangement of the lock recesses. Preferred Features: The distance between the free end of the key tip and the next lock recess is shorter than the distance between the lock recesses.

IPC 8 full level

E05B 19/06 (2006.01); **E05B 19/00** (2006.01); **E05B 27/04** (2006.01)

CPC (source: EP)

E05B 19/0017 (2013.01); **E05B 17/007** (2013.01); **E05B 19/0058** (2013.01)

Citation (search report)

- [XA] DE 19745834 A1 19990422 - WINKHAUS FA AUGUST [DE]
- [X] AT 395262 B 19921110 - EVVA WERKE [AT]
- [X] US 4098104 A 19780704 - WOLTER HEINZ [DE]
- [X] US 3777520 A 19731211 - CREPINSEK A
- [X] AU 714767 B2 20000113 - MEDECO SECURITY LOCKS
- [X] US 1977189 A 19341016 - LARSON IVAR G, et al

Cited by

EP2149657A1; EP2146030A1; EP2264264A3; EP2746500A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

EP 1577469 A2 20050921; **EP 1577469 A3 20060419**; **EP 1577469 B1 20091111**; AT E448376 T1 20091115; DE 102004013522 A1 20051006; DE 502005008464 D1 20091224; DK 1577469 T3 20100308; ES 2334446 T3 20100310; PL 1577469 T3 20100430; SI 1577469 T1 20100331

DOCDB simple family (application)

EP 05101380 A 20050223; AT 05101380 T 20050223; DE 102004013522 A 20040319; DE 502005008464 T 20050223; DK 05101380 T 20050223; ES 05101380 T 20050223; PL 05101380 T 20050223; SI 200530902 T 20050223