

Title (en)

Turbomachine with two sub-assemblies being under axial pressure

Title (de)

Turbomaschine mit zwei unter axialer Spannung stehenden Unterteilen

Title (fr)

Turbomachine comprenant deux sous-ensembles assemblés sous contrainte axiale

Publication

EP 1580402 B1 20070718 (FR)

Application

EP 05290663 A 20050325

Priority

FR 0403128 A 20040326

Abstract (en)

[origin: EP1580402A1] The turbomachine has two sub-assemblies assembled together. One of the assemblies has an outer case while the other assembly has a support for fixed vanes of the machine, where the case and the support define, between them, an annular chamber (18) within which a pressure seal (20) is inserted. An annular spacer (50) is inserted between a circular region of the former assembly and a circular end of a flat surface of the latter assembly.

IPC 8 full level

F01D 11/00 (2006.01); **F01D 25/24** (2006.01); **F04D 29/08** (2006.01); **F16J 15/08** (2006.01)

CPC (source: EP US)

F01D 11/005 (2013.01 - EP US)

Designated contracting state (EPC)

DE ES FR GB IT SE

DOCDB simple family (publication)

FR 2868125 A1 20050930; FR 2868125 B1 20060721; CA 2500947 A1 20050926; CA 2500947 C 20121120; DE 602005001641 D1 20070830; DE 602005001641 T2 20080605; EP 1580402 A1 20050928; EP 1580402 B1 20070718; ES 2290863 T3 20080216; JP 2005291203 A 20051020; JP 4643326 B2 20110302; RU 2005108494 A 20060927; RU 2380546 C2 20100127; UA 86354 C2 20090427; US 2005260066 A1 20051124; US 7571614 B2 20090811

DOCDB simple family (application)

FR 0403128 A 20040326; CA 2500947 A 20050323; DE 602005001641 T 20050325; EP 05290663 A 20050325; ES 05290663 T 20050325; JP 2005085761 A 20050324; RU 2005108494 A 20050325; UA A200502763 A 20050325; US 8635905 A 20050323