

Title (en)

Reeling machine for continuous winding of a web material

Title (de)

Wickelmaschine zum kontinuierlichen Aufwickeln einer Materialbahn

Title (fr)

Bobineuse pour le bobinage continu d'une bande de matériau

Publication

EP 1591390 B1 20080227 (DE)

Application

EP 05103314 A 20050425

Priority

DE 102004020322 A 20040426

Abstract (en)

[origin: EP1591390A1] The air expulsion device (10) for consolidating the web layers and regulating the amount of air trapped in between them comprises a number of adjacent segment rolls (11) with their opposite ends mounted via bearing units (12) on a support profile (13) extending the width of the machine. The bearing units have a counter-bearing (14) and a resilient bearing (15) on the profile side. The counter-bearing is a hinge bearing. The resilient bearing is a preferably closed spring system, preferably a coil or leaf spring, or a preferably closed damping unit, preferably a shock absorber, or a controllable hydraulic or pneumatic piston unit.

IPC 8 full level

B65H 18/26 (2006.01); **B65H 19/22** (2006.01)

CPC (source: EP)

B65H 18/26 (2013.01); **B65H 19/2207** (2013.01); **B65H 19/2261** (2013.01); **B65H 2408/2364** (2013.01)

Cited by

CN102803108A; EP3103748A1; AT510884A1; AT510884B1; US9926159B2; WO2010149404A1; WO2010004029A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

EP 1591390 A1 20051102; **EP 1591390 B1 20080227**; AT E387393 T1 20080315; DE 102004020322 A1 20051110;
DE 502005002951 D1 20080410

DOCDB simple family (application)

EP 05103314 A 20050425; AT 05103314 T 20050425; DE 102004020322 A 20040426; DE 502005002951 T 20050425