

Title (en)

Connecting arrangement with a plastic carrier part and a plastic thread element

Title (de)

Verbindungsanordnung mit einem Kunststoff-Trägerteil und einem Kunststoff-Gewindeelement

Title (fr)

Arrangement de relation avec une pièce en plastique de porteur et un élément en plastique de fil

Publication

EP 1591675 A2 20051102 (DE)

Application

EP 05009142 A 20050426

Priority

DE 102004021484 A 20040430

Abstract (en)

A joining assembly comprises a threaded element of plastic material comprising a core and an external threaded portion. A joining assembly (1) comprises a support member (2) of plastic material having a receiving bore defined by a bore wall, and a threaded element (4) of plastic material comprising a core (8) and an external threaded portion (10) which, when the threaded element is threaded into the wall of the receiving bore of the support member forms an internal threaded portion in the receiving bore by a cutting and/or deforming operation. The external threaded portion of the threaded element comprises a thread extending for revolutions and being, in axial cross-section, of a profile having straight flanks that are joined by a rounded crest. The core of the threaded element has, between the revolutions of the thread, a cylindrical external surface, which, in an axial cross-section, is joined to the flanks of the thread by rounded corners. The revolution of the thread defines a helical gap of a volume exceeding that of the thread. Independent claims are also included for: (1) a tool for making a joining assembly, comprising a tool body comprising an axially extending mandrel and an abutment portion, the mandrel comprising an axially extending pin having a short threaded portion adjacent the abutment portion and a cylindrical support portion adjacent the threaded portion; (2) a threaded element for a joining assembly, comprising a screw; and (3) a method for making a joining assembly, comprising threading the threaded element into the receiving bore of the support member at a high speed so that the plastic material of the support member is plastified by friction and the plastified plastic material is displaced from the external thread of the threaded element in a direction opposite to the threading direction to provide an encapsulating enclosure of the external thread when the plastified plastic material has been solidified.

Abstract (de)

Das aus Kunststoff bestehende Gewindeelement (4,6) für diese Verbindungsanordnung hat ein speziell ausgebildetes Gewindeprofil mit einem kleinen Profilwinkel (α) zwischen 30° und 50° und einer relativ großen Rundung (31) an den Flankenspitzen, wobei der Freiraum zwischen den Windungen des Gewindeganges (11) ein größeres Volumen als der Gewindegang hat. Um eine spezielle Schneidgeometrie des Gewindeprofils zu erzeugen, besteht das Gewindeelement (4,6) aus mehreren Winkelsegmenten, die radial gegeneinander so versetzt sind, dass jeweils benachbarte Winkelsegmente in Einschraubrichtung wirksame Schneidkanten bilden. Beschrieben werden außerdem ein Werkzeug und ein Verfahren zum Herstellen einer derartigen Verbindungsanordnung. <IMAGE>

IPC 1-7

F16B 25/10; **F16B 33/00**; **F16B 33/02**

IPC 8 full level

F16B 23/00 (2006.01); **F16B 25/00** (2006.01); **F16B 25/06** (2006.01); **F16B 25/10** (2006.01); **F16B 33/00** (2006.01); **F16B 33/02** (2006.01); **F16B 35/00** (2006.01)

CPC (source: BR EP US)

F16B 25/0015 (2013.01 - EP US); **F16B 25/0047** (2013.01 - EP US); **F16B 25/0052** (2013.01 - EP US); **F16B 25/10** (2013.01 - EP US); **F16B 33/006** (2013.01 - EP US); **F16B 33/02** (2013.01 - EP US); **F16B 35/005** (2013.01 - BR); **Y10S 411/908** (2013.01 - EP US)

Cited by

EP2703659A1; EP3910126A1; DE202006016165U1; RU2683390C1; US10954987B2; WO2014195336A1; WO2018115006A1; WO2018007069A1; US8337132B2; US10730494B2; EP2019210A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

EP 1591675 A2 20051102; **EP 1591675 A3 20060607**; **EP 1591675 B1 20061206**; AT E347659 T1 20061215; AT E386888 T1 20080315; BR PI0501444 A 20060110; BR PI0501444 B1 20180529; CA 2505770 A1 20051030; CA 2505770 C 20090224; CN 100467887 C 20090311; CN 101216062 A 20080709; CN 101216062 B 20111012; CN 1693723 A 20051109; DE 102004021484 A1 20051124; DE 102004021484 B4 20181129; DE 502005000215 D1 20070118; DE 502005002919 D1 20080403; EP 1715198 A2 20061025; EP 1715198 A3 20070606; EP 1715198 B1 20080220; ES 2277308 T3 20070701; ES 2302273 T3 20080701; JP 2005315425 A 20051110; JP 2007315609 A 20071206; JP 4118899 B2 20080716; JP 4118940 B2 20080716; MX PA05004625 A 20051103; PL 1591675 T3 20070430; PL 1715198 T3 20080731; US 2005244249 A1 20051103; US 2008213065 A1 20080904; US 7658581 B2 20100209

DOCDB simple family (application)

EP 05009142 A 20050426; AT 05009142 T 20050426; AT 06008935 T 20050426; BR PI0501444 A 20050429; CA 2505770 A 20050427; CN 200510068403 A 20050429; CN 200710181683 A 20050429; DE 102004021484 A 20040430; DE 502005000215 T 20050426; DE 502005002919 T 20050426; EP 06008935 A 20050426; ES 05009142 T 20050426; ES 06008935 T 20050426; JP 2005128373 A 20050426; JP 2007224962 A 20070831; MX PA05004625 A 20050429; PL 05009142 T 20050426; PL 06008935 T 20050426; US 11924705 A 20050429; US 7905008 A 20080324