

Title (en)

METHOD FOR PROVIDING FLAT TUBE DESIGNS FOR AN AUTOMOTIVE HEAT EXCHANGER

Title (de)

VERFAHREN ZUR AUSLEGUNG VON FLACHROHREN FÜR KRAFTFAHRZEUG-WÄRMETAUSCHER

Title (fr)

PROCÉDÉ POUR LA CONFIGURATION DE TUBES PLATS POUR ÉCHANGEUR DE CHALEUR DE VÉHICULE AUTOMOBILE

Publication

**EP 1608928 A1 20051228 (EN)**

Application

**EP 04721949 A 20040319**

Priority

- GB 2004001215 W 20040319
- GB 0306269 A 20030319

Abstract (en)

[origin: GB2399623A] A flat tube heat exchanger comprises tubes 1 having a plurality of non-circular cross-sectional shaped flow channels 2 extending in a longitudinal direction of the tubes 1. Tubes 1 maybe extruded aluminium, extend between headers and stacked in rows with fins in thermal contact with adjacent spaced tubes for the passage of air to increase heat transfer. Channels 2 may communicate high pressure carbon dioxide refrigerant and maybe triangular and arranged in tessellating relationship, rectangular, or rectangular with a waist portion mid way along its width (fig 5). The shape of the tubes 1 reduces the weight of the heat exchanger, increases heat transfer conductance of the heat exchanger using a high pressure refrigerant and also offers good strength characteristics.

IPC 1-7

**F28F 1/02; F28D 1/053; F28F 1/04**

IPC 8 full level

**F28D 1/053 (2006.01); F28F 1/02 (2006.01); F28F 1/04 (2006.01)**

CPC (source: EP)

**F28D 1/05383 (2013.01); F28F 1/022 (2013.01); F28F 1/045 (2013.01); F28D 2021/0073 (2013.01); F28F 2255/16 (2013.01)**

Citation (search report)

See references of WO 2004083762A1

Cited by

EP3492853A1

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

**GB 0306269 D0 20030423; GB 2399623 A 20040922; DE 602004029338 D1 20101111; EP 1608928 A1 20051228; EP 1608928 B1 20100929; WO 2004083762 A1 20040930**

DOCDB simple family (application)

**GB 0306269 A 20030319; DE 602004029338 T 20040319; EP 04721949 A 20040319; GB 2004001215 W 20040319**