

Title (en)

Insulated electrical conductor with preserved functionality in case of fire

Title (de)

Isolierter elektrischer Leiter mit Funktionserhalt im Brandfall

Title (fr)

conducteur électrique isolé continuant à fonctionner en cas d'incendie

Publication

EP 1619694 A1 20060125 (DE)

Application

EP 04291877 A 20040723

Priority

EP 04291877 A 20040723

Abstract (en)

An electrical conductor consists of a metallic conductor (1) with a glass / mica layer on top, and a surrounding plastic layer. The glass / mica layer consists of two band sections. The first band (2) has edges which overlap by 25-50%. The second band (4) has an inner mica layer and is wound around the first band, with edges that overlap between 25-50%. The plastic layer (5) contains a material, which forms a ceramic in the event of a fire.

IPC 8 full level

H01B 7/02 (2006.01); **H01B 7/18** (2006.01); **H01B 7/29** (2006.01); **H01B 7/295** (2006.01)

CPC (source: EP)

H01B 3/04 (2013.01); **H01B 3/08** (2013.01); **H01B 7/295** (2013.01); **H01B 7/0241** (2013.01); **H01B 7/0258** (2013.01)

Citation (search report)

- [X] EP 1199728 A2 20020424 - NEXANS [FR]
- [XY] US 2002046871 A1 20020425 - GOEBLMAIER REINHOLD [DE], et al
- [Y] WO 9602920 A1 19960201 - RAYCHEM LTD [GB], et al
- [Y] FR 2573910 A1 19860530 - HABIA CABLE [FR]

Cited by

CN113921190A; EP3937191A1; JP2022014885A; WO2016128785A1; US10453588B2; WO2017130016A1; US11276511B2

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

EP 1619694 A1 20060125; EP 1619694 B1 20120905; PL 1619694 T3 20130228

DOCDB simple family (application)

EP 04291877 A 20040723; PL 04291877 T 20040723