

Title (en)  
OPERATING DEVICE

Title (de)  
BEDIENEINRICHTUNG

Title (fr)  
DISPOSITIF DE COMMANDE

Publication  
**EP 1623392 B1 20100512 (DE)**

Application  
**EP 04728168 A 20040419**

Priority  
• EP 2004004151 W 20040419  
• DE 10321230 A 20030512

Abstract (en)  
[origin: WO2004100079A1] The invention relates to a splashproof operating device (1), especially of a tachograph. A faulty seal often results in the entire apparatus breaking down because the fault remains undiscovered. The aim of the invention is to create an operating device (1) that ensures good functional safety and seals well towards the surroundings with the adjacent components. Said aim is achieved by an operating device in which contact areas (17) are elastically braced against each other. A decisive advantage of the inventive operating device consists of the fact that the abutting contact areas (17) of the operating element (9) are braced.

IPC 8 full level  
**G07C 7/00** (2006.01)

CPC (source: EP US)  
**G07C 7/00** (2013.01 - EP US)

Citation (examination)  
• US 2355303 A 19440808 - KNUD KNUDSEN  
• BEITZ W.; KÜTTNER K.-H.: "Dubbel - Taschenbuch für den Maschinenbau", 1987, SPRINGER VERLAG, BERLIN HEIDELBERG NEW YORK LONDON PARIS TOKYO, ISBN: 3-540-18009-5

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)  
**WO 2004100079 A1 20041118**; AT E467877 T1 20100515; BR PI0410257 A 20060516; BR PI0410257 B1 20170502; CN 1802669 A 20060712; CN 1802669 B 20101208; DE 10321230 A1 20041209; DE 10321230 B4 20090402; DE 502004011157 D1 20100624; EP 1623392 A1 20060208; EP 1623392 B1 20100512; JP 2006526199 A 20061116; US 2006249363 A1 20061109

DOCDB simple family (application)  
**EP 2004004151 W 20040419**; AT 04728168 T 20040419; BR PI0410257 A 20040419; CN 200480011703 A 20040419; DE 10321230 A 20030512; DE 502004011157 T 20040419; EP 04728168 A 20040419; JP 2006505192 A 20040419; US 55441905 A 20051024