

Title (en)

METHOD FOR PRODUCTION OF A SEALING JOINT GASKET

Title (de)

VERFAHREN ZUR HERSTELLUNG EINES DICHTUNGSSTRANGES

Title (fr)

PROCEDE DE FABRICATION D'UN CORDON DE JOINT D'ETANCHEITE

Publication

EP 1646699 A1 20060419 (FR)

Application

EP 04739238 A 20040518

Priority

- EP 2004005335 W 20040518
- FR 0306122 A 20030522

Abstract (en)

[origin: FR2855230A1] The procedure for making sealant bead of required cross-section comprises creating supple elastic core (I)(5a) and moisture repellent skin by applying it to core, coextruding 2 different materials or extruding material that forms skin. (I) has relative density of 0.5, especially 0.1-0.4. The bead has force of pressure of 0.5-1.5 N/cm. In a variant the outer surface of the bead can be adhesive.

IPC 1-7

C09K 3/10; **B60R 13/06**

IPC 8 full level

B60J 5/04 (2006.01); **B60R 13/08** (2006.01); **C09K 3/10** (2006.01)

CPC (source: EP KR)

B60J 5/04 (2013.01 - KR); **B60J 5/0418** (2013.01 - EP); **B60R 13/08** (2013.01 - KR); **B60R 13/0892** (2013.01 - EP); **C09K 3/10** (2013.01 - KR); **C09K 3/1021** (2013.01 - EP)

Citation (search report)

See references of WO 2004104133A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

FR 2855230 A1 20041126; **FR 2855230 B1 20050729**; EP 1646699 A1 20060419; JP 2007502354 A 20070208; KR 20060025530 A 20060321; WO 2004104133 A1 20041202

DOCDB simple family (application)

FR 0306122 A 20030522; EP 04739238 A 20040518; EP 2004005335 W 20040518; JP 2006529859 A 20040518; KR 20057021922 A 20051117