

Title (en)

DRILLING/ROLLING METHOD IN MANUFACTURING SEAMLESS TUBE

Title (de)

BOHR-/WALZVERFAHREN BEI DER HERSTELLUNG VON NAHTLOSEN ROHREN

Title (fr)

PROCEDE DE PER AGE/LAMINAGE DESTINE A LA FABRICATION D'UN TUBE SANS SOUDURE

Publication

EP 1649945 A4 20070418 (EN)

Application

EP 04745554 A 20040603

Priority

- JP 2004007698 W 20040603
- JP 2003162416 A 20030606

Abstract (en)

[origin: EP1649945A1] A piercing method for manufacturing a seamless pipe capable of suppressing the rotary forging effects and suppressing the redundant shear strain without excessive narrowing of the roll diameter is provided. This method is characterized by holding a feed angle α^2 and a cross angle β^3 of main rolls in a range satisfying the following expressions (1) to (3), setting the relationship between outer diameter "do" of the solid billet and the outer diameter "d" and thickness "t" of a hollow piece after piercing so as to satisfy the following expression (4), and further setting the relationship between inlet diameter D 1 and outlet diameter D 2 of the main roll with the above-mentioned "do", "d" and β^3 so as to satisfy the following expression (5). $8^\circ \leq \alpha^2 \leq 20^\circ$, $5^\circ \leq \beta^3 \leq 35^\circ$, $15^\circ \leq \alpha^2 + \beta^3 \leq 50^\circ$, $1.5 \leq \frac{d}{d_0} \leq 4.5$, $0.75 + 0.025 \leq \frac{D_2}{D_1} \leq 1$ In the expression (4), $r = \ln(2t/d_0)$ and $r'' = \ln(2(d/t)/d_0)$

IPC 8 full level

B21B 19/04 (2006.01)

CPC (source: EP)

B21B 19/04 (2013.01)

Citation (search report)

- [A] DE 3844802 C2 19950511 - SUMITOMO METAL IND [JP]
- [A] GB 2202778 A 19881005 - SUMITOMO METAL IND
- [A] JP S6431505 A 19890201 - SUMITOMO METAL IND
- [A] DE 3212742 A1 19821104 - SUMITOMO METAL IND [JP]
- [A] DE 2054541 A1 19710519
- See references of WO 2004108310A1

Cited by

EP2052795A4; EP3120942A4

Designated contracting state (EPC)

DE IT

DOCDB simple family (publication)

EP 1649945 A1 20060426; EP 1649945 A4 20070418; EP 1649945 B1 20110126; CN 100509192 C 20090708; CN 1795060 A 20060628; DE 602004031232 D1 20110310; JP 4196991 B2 20081217; JP WO2004108310 A1 20060720; RU 2005141132 A 20060627; RU 2309810 C2 20071110; WO 2004108310 A1 20041216

DOCDB simple family (application)

EP 04745554 A 20040603; CN 200480014144 A 20040603; DE 602004031232 T 20040603; JP 2004007698 W 20040603; JP 2005506775 A 20040603; RU 2005141132 A 20040603