

Title (en)
DRILLING/ROLLING METHOD IN MANUFACTURING SEAMLESS TUBE

Title (de)
BOHR-/WALZVERFAHREN BEI DER HERSTELLUNG VON NAHTLOSEN ROHREN

Title (fr)
PROCEDE DE PER AGE/LAMINAGE DESTINE A LA FABRICATION D'UN TUBE SANS SOUDURE

Publication
EP 1649945 B1 20110126 (EN)

Application
EP 04745554 A 20040603

Priority
• JP 2004007698 W 20040603
• JP 2003162416 A 20030606

Abstract (en)
[origin: EP1649945A1] A piercing method for manufacturing a seamless pipe capable of suppressing the rotary forging effects and suppressing the redundant shear strain without excessive narrowing of the roll diameter is provided. This method is characterized by holding a feed angle ² and a cross angle ³ of main rolls in a range satisfying the following expressions (1) to (3), setting the relationship between outer diameter "do" of the solid billet and the outer diameter "d" and thickness "t" of a hollow piece after piercing so as to satisfy the following expression (4), and further setting the relationship between inlet diameter D 1 and outlet diameter D 2 of the main roll with the above-mentioned "do", "d" and ³ so as to satisfy the following expression (5). $8^{\circ} \leq \alpha^2 \leq 20^{\circ}$, $5^{\circ} \leq \alpha^3 \leq 35^{\circ}$, $15^{\circ} \leq \alpha^2 + \alpha^3 \leq 50^{\circ}$, $1.5 \leq \frac{r}{t} \leq 4.5$, $\frac{d}{do} / (0.75 + 0.025 \alpha^3) \leq D2 / D1$ In the expression (4), $r = \ln(2t / d0)$ and $\alpha = \ln\{2(d / t) / d0\}$

IPC 8 full level
B21B 19/04 (2006.01)

CPC (source: EP)
B21B 19/04 (2013.01)

Cited by
EP3120942A4; EP2052795A4

Designated contracting state (EPC)
DE IT

DOCDB simple family (publication)
EP 1649945 A1 20060426; EP 1649945 A4 20070418; EP 1649945 B1 20110126; CN 100509192 C 20090708; CN 1795060 A 20060628; DE 602004031232 D1 20110310; JP 4196991 B2 20081217; JP WO2004108310 A1 20060720; RU 2005141132 A 20060627; RU 2309810 C2 20071110; WO 2004108310 A1 20041216

DOCDB simple family (application)
EP 04745554 A 20040603; CN 200480014144 A 20040603; DE 602004031232 T 20040603; JP 2004007698 W 20040603; JP 2005506775 A 20040603; RU 2005141132 A 20040603