

Title (en)

ELECTRICAL FEEDTHROUGHS FOR ULTRAVACUUM APPLICATION

Title (de)

ELEKTRISCHE DURCHSPEISUNGEN FÜR UKLTRA VAKUUM-ANWENDUNG

Title (fr)

TRAVERSEES ELECTRIQUES MULTIPLES DESTINEES A DES APPLICATIONS DE VIDE POUSSÉ A DES TEMPERATURES DE FONCTIONNEMENT COMPRISES ENTRE 70 ET 530 oK

Publication

EP 1658657 A1 20060524 (EN)

Application

EP 03818409 A 20030827

Priority

IT 0300519 W 20030827

Abstract (en)

[origin: WO2005022694A1] A device that provides for the passage of an electrical current through a wall of separation of rooms operating under even very different thermal, atmospheric conditions. The invention uses metal leads fitted with interference into one or more adjacent coaxial discs of plastic materials with high electrical, mechanical, thermal, chemical resistance to provide the electrical feedthroughs. An embodiment of the invention (Fig. 1) consists of electrical feedthroughs formed of one or more cylindrical metal leads (6) that have a short length with larger diameter which interferes with the corresponding hole of the discs of plastic material (5, 5'), thus ensuring the vacuum tightness. The discs (5, 5') are located between and pressed by two adjacent, coaxial metal rings (2, 3) rigidly connected to each other by sealing. Metal ring (2) is sealed to the wall and provides for the separation of the rooms and the passage of the electrical current- Components (4, 1) can be threaded at their outer surfaces to allow electrical connectors to be used.

IPC 1-7

H01R 4/68

IPC 8 full level

H01R 13/533 (2006.01)

CPC (source: EP)

H01R 13/533 (2013.01); **H01R 13/74** (2013.01); **H01R 13/521** (2013.01)

Citation (examination)

- US 3897131 A 19750729 - STAUFFER LARRY RONALD
- EP 0580498 A1 19940126 - GEC ALSTHOM ELECTROMEC [FR]

Cited by

EP2458692A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PT RO SE SI SK TR

DOCDB simple family (publication)

WO 2005022694 A1 20050310; AU 2003265145 A1 20050316; EP 1658657 A1 20060524

DOCDB simple family (application)

IT 0300519 W 20030827; AU 2003265145 A 20030827; EP 03818409 A 20030827