

Title (en)
Light source

Title (de)
Leuchtmittel

Title (fr)
Source lumineuse

Publication
EP 1659617 A1 20060524 (DE)

Application
EP 04027383 A 20041118

Priority
EP 04027383 A 20041118

Abstract (en)
The illuminant has proximal and distal burner connections (19, 20), which are diametrically connected with respective proximal and distal end areas of a bulb (17) from a burner. Supply lines (23, 24) are led into the bulb via a U-shaped squeezer and are connected with the respective connections. The squeezer has an additional open space (26) into which the connection (19) and burner are inserted. An independent claim is also included for a reflector lamp comprising an outer jacket built as a reflector.

IPC 8 full level
H01J 61/36 (2006.01); **H01J 61/34** (2006.01)

CPC (source: EP US)
H01J 61/34 (2013.01 - EP US); **H01J 61/36** (2013.01 - EP US)

Citation (search report)

- [XA] US 2001003411 A1 20010614 - HONDA HISASHI [JP], et al
- [XA] EP 0981151 A1 20000223 - USHIO ELECTRIC INC [JP]
- [DA] EP 1383159 A2 20040121 - SLI LICHTSYSTEME GMBH [DE]

Cited by
EP1975975A1; WO2007063059A1; WO2008119623A1; WO2008119606A1; DE102007015483A1; DE102007015481A1; US7977854B2

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)
EP 1659617 A1 20060524; EP 1659617 B1 20070228; AT E355610 T1 20060315; DE 502004003074 D1 20070412; ES 2283926 T3 20071101; US 2006197422 A1 20060907; US 7642716 B2 20100105

DOCDB simple family (application)
EP 04027383 A 20041118; AT 04027383 T 20041118; DE 502004003074 T 20041118; ES 04027383 T 20041118; US 27279305 A 20051115