

Title (en)  
DISPLAY SYSTEMS FOR A DEVICE

Title (de)  
DISPLAY-SYSTEME FÜR EIN GERÄT

Title (fr)  
SYSTEMES D'AFFICHAGE POUR UN APPAREIL

Publication  
**EP 1661117 A4 20090121 (EN)**

Application  
**EP 04817726 A 20040701**

Priority

- US 2004023167 W 20040701
- US 61563403 A 20030708
- US 61614503 A 20030708
- US 61984803 A 20030714
- US 70667203 A 20031111

Abstract (en)  
[origin: WO2005050601A2] A display system for a operating a device receives images from a first sensor and a second sensor that represent scenery outside the device. The display system is configured to detect moving objects in the images, as well as fuse the images to a single viewpoint. The fused image is transformed to a first viewpoint image from a first operator station in the device, and a second viewpoint image from a second operator station in the device. The combined sensor image and symbols are output to a display device that is positioned to provide a portion of the out-the-window field of view to the operator. The entire desired field of view for the operator is provided by the display device in combination with the out-the-window scene available through windows of the device. The display system generates a plurality of mutually exclusive windows on a display device. One or more of the windows includes a common user interface and a common display area for a subset of at least two of the windows. The system receives information regarding current flight conditions of the device such as an aircraft and determines the acoustic level of the sonic boom and/or other noise generated by the device during operation. The current acoustic level is compared to a desired level, and various cues are displayed to operators regarding corrective actions that can be taken to reduce or maintain the acoustic level at the desired level. A protective housing encloses the sensors. This protective housing includes a transparent aperture through which the sensor captures images. A cleaning mechanism removes obstructions from the transparent aperture in order to provide continuous images representing scenery outside the device through an operator display.

IPC 8 full level  
**G09G 5/00** (2006.01); **B64D 47/08** (2006.01); **G01C 23/00** (2006.01)

IPC 8 main group level  
**G09G** (2006.01)

CPC (source: EP US)  
**B64D 43/00** (2013.01 - EP); **B64D 47/08** (2013.01 - EP US); **G01C 23/005** (2013.01 - EP)

Citation (search report)

- [X] US 5189929 A 19930302 - CHORY ANTHONY G [US]
- [XA] US 2003067542 A1 20030410 - MONROE DAVID A [US]
- [A] US 5742336 A 19980421 - LEE FREDERICK A [US]
- [A] WO 9816421 A1 19980423 - BULLOCK RODDY M [US], et al
- [XA] GUELL J: "FLILO (Flying Infrared for Low-level Operations) an Enhanced Vision System", IEEE AEROSPACE AND ELECTRONIC SYSTEMS MAGAZINE, IEEE SERVICE CENTER, PISCATAWAY, NJ, US, 1 September 2000 (2000-09-01), pages 31 - 35, XP002988590, ISSN: 0885-8985
- See references of WO 2005050601A2

Designated contracting state (EPC)  
FR GB

DOCDB simple family (publication)  
**WO 2005050601 A2 20050602; WO 2005050601 A3 20060406; EP 1661117 A2 20060531; EP 1661117 A4 20090121**

DOCDB simple family (application)  
**US 2004023167 W 20040701; EP 04817726 A 20040701**