

Title (en)
SELF-DRILLING ANCHOR

Title (de)
SELBSTBOHRENDER ANKERBOLZEN

Title (fr)
ANCRAGE AUTOPERCEUR

Publication
EP 1676035 A1 20060705 (EN)

Application
EP 04793935 A 20041001

Priority

- US 2004032281 W 20041001
- US 51070803 P 20031010
- US 93491304 A 20040903
- US 84470604 A 20040512

Abstract (en)
[origin: US2005084360A1] A self-drilling anchor for use in a friable material comprises a body having an axis, an axial bore adapted to receive a fastener, a proximal end, a drilling end, a proximal portion adjacent the proximal end having threading for engaging the friable material, and a drilling portion adjacent the drilling end, wherein the threading has a root with a root diameter and a crest with a crest diameter, and the anchor has a head at the proximal end having an outer diameter that is smaller than the crest diameter. The anchor head is configured for minimizing visible distortion of the friable material as the anchor is advanced into the friable material.

IPC 1-7
F16B 37/12; F16B 13/00

IPC 8 full level
E04B 1/48 (2006.01); **F16B 13/00** (2006.01); **F16B 25/00** (2006.01); **F16B 25/04** (2006.01); **F16B 25/06** (2006.01); **F16B 25/10** (2006.01);
F16B 35/04 (2006.01); **F16B 37/12** (2006.01)

CPC (source: EP US)
F16B 13/002 (2013.01 - EP US); **F16B 37/127** (2013.01 - EP US)

Citation (search report)
See references of WO 2005038275A1

Designated contracting state (EPC)
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)
US 2005084360 A1 20050421; AU 2004282503 A1 20050428; CA 2541433 A1 20050428; EP 1676035 A1 20060705; EP 1676035 B1 20131211;
JP 2007527487 A 20070927; JP 4602984 B2 20101222; MX PA06003995 A 20060705; NZ 546479 A 20080829; WO 2005038275 A1 20050428

DOCDB simple family (application)
US 93491304 A 20040903; AU 2004282503 A 20041001; CA 2541433 A 20041001; EP 04793935 A 20041001; JP 2006534126 A 20041001;
MX PA06003995 A 20041001; NZ 54647904 A 20041001; US 2004032281 W 20041001