

Title (en)  
Printhead carriage

Title (de)  
Druckkopfwagen

Title (fr)  
Chariot de tête d'impression

Publication  
**EP 1676711 A1 20060705 (EN)**

Application  
**EP 05112665 A 20051221**

Priority  
• EP 04107044 A 20041229  
• EP 05112665 A 20051221

Abstract (en)  
A printhead carriage comprising a body (10) that is guided and driven for reciprocating movement in a printer, a mounting plate (12) for a printhead assembly, and a suspension structure (14) adjustably connecting the mounting plate (12) to the body (10), the suspension structure (14) comprising a framework of hinge plates (32, 34) having elastic hinges (50; 72) that are formed by portions of the hinge plates where the width thereof is reduced, and at least one adjusting mechanism (36, 40; 38, 42; 44) adapted to adjust the position of the mounting plate (12) by elastically deflecting at least one of the hinges, characterized in that an adjusting unit (20; 24) for at least one degree of freedom of the mounting plate (12) comprises two hinge plates (32, 34) that are connected to a common support point (26; 28; 30) of the mounting plate (12) and are oriented at right angles relative to one another, and an adjusting mechanism (36, 40; 38, 42; 44) adapted to push and/or pull one hinge plate (32) in longitudinal direction thereof, with elastic deflection of at least one hinge of the other hinge plate (34).

IPC 8 full level  
**B41J 25/304** (2006.01); **B41J 2/175** (2006.01)

CPC (source: EP)  
**B41J 2/1752** (2013.01); **B41J 25/304** (2013.01); **B41J 2202/14** (2013.01)

Citation (applicant)  
EP 0693382 A1 19960124 - OCE NEDERLAND BV [NL]

Citation (search report)  
[DA] EP 0693382 A1 19960124 - OCE NEDERLAND BV [NL]

Cited by  
EP3463918A4; US10046580B2; WO2022023851A1

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)  
**EP 1676711 A1 20060705; EP 1676711 B1 20071024**

DOCDB simple family (application)  
**EP 05112665 A 20051221**