

Title (en)
METHOD OF MAKING A MEMS ELECTROSTATIC CHUCK

Title (de)
VERFAHREN ZUR HERSTELLUNG EINER ELEKTROSTATISCHEN MEMS-EINSPANNVORRICHTUNG

Title (fr)
PROCEDE DE FABRICATION D'UN MANDRIN ELECTROSTATIQUE A MEMS

Publication
EP 1678752 B1 20070523 (EN)

Application
EP 04796693 A 20041028

Priority
• US 2004035891 W 20041028
• US 69515303 A 20031028

Abstract (en)
[origin: US2005099758A1] The present invention is directed to a method of forming a clamping plate for a multi-polar electrostatic chuck. The method comprises forming a first electrically conductive layer over a semiconductor platform and defining a plurality of portions of the first electrically conductive layer which are electrically isolated from one another. A first electrically insulative layer is formed over the first electrically conductive layer, the first electrically insulative layer comprising a top surface having a plurality of MEMS protrusions extending a first distance therefrom. A plurality of poles are furthermore electrically connected to the respective plurality of portions of the first electrically conductive layer, wherein a voltage applied between the plurality of poles is operable to induce an electrostatic force in the clamping plate.

IPC 8 full level
H01L 21/68 (2006.01); **H01L 21/683** (2006.01)

CPC (source: EP KR US)
B81C 1/00 (2013.01 - KR); **H01L 21/6833** (2013.01 - EP US); **H01L 21/687** (2013.01 - KR)

Designated contracting state (EPC)
DE FR GB IT

DOCDB simple family (publication)
US 2005099758 A1 20050512; **US 6946403 B2 20050920**; CN 100524683 C 20090805; CN 1894788 A 20070110;
DE 602004006639 D1 20070705; DE 602004006639 T2 20080131; EP 1678752 A1 20060712; EP 1678752 B1 20070523;
JP 2007510310 A 20070419; JP 4725740 B2 20110713; KR 20060092245 A 20060822; TW 200518144 A 20050601; TW I360856 B 20120321;
WO 2005045921 A1 20050519

DOCDB simple family (application)
US 69515303 A 20031028; CN 200480032031 A 20041028; DE 602004006639 T 20041028; EP 04796693 A 20041028;
JP 2006538273 A 20041028; KR 20067007513 A 20060419; TW 93132546 A 20041027; US 2004035891 W 20041028