

Title (en)  
Lock cylinder

Title (de)  
Schließzylinder

Title (fr)  
Serrure cylindrique

Publication  
**EP 1679413 A3 20061025 (DE)**

Application  
**EP 05111728 A 20051206**

Priority  
DE 102005001067 A 20050107

Abstract (en)  
[origin: EP1679413A2] Closing cylinder comprises a rocking arm (10) pivoting in a housing (1) or in a core (2) and penetrating a groove (15) in an opposite-lying component, in which the groove has a pocket facing the front side of the core. The rocking arm is pre-tensioned by the pocket by a spring force or by gravity. The rocking arm is made from a magnetic material. Preferred Features: The rocking arm is positioned in the housing and the groove is arranged peripherally in the core. The groove has a protrusion in the direction of the pocket. The rocking arm is pre-tensioned by a spring element (13) formed as a pressure spring or rotary spring.

IPC 8 full level  
**E05B 9/04** (2006.01); **E05B 47/06** (2006.01)

CPC (source: EP)  
**E05B 47/063** (2013.01); **E05B 47/0004** (2013.01); **E05B 2047/0092** (2013.01)

Citation (search report)

- [XY] FR 2687426 A1 19930820 - BRICARD SA [FR]
- [YA] DE 3208818 A1 19830929 - WINKHAUS FA AUGUST [DE]
- [A] DE 19613460 A1 19971016 - HOEPPER RICHARD [DE]
- [A] US 4761976 A 19880809 - KLEINHANY ARNO [CH]
- [A] US 4789859 A 19881206 - CLARKSON BRUCE A [US], et al
- [A] EP 1378620 A2 20040107 - DOM SICHERHEITSTECHNIK [DE]

Cited by  
CN104074410A; EP3670795A1

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

Designated extension state (EPC)  
AL BA HR MK YU

DOCDB simple family (publication)  
**EP 1679413 A2 20060712; EP 1679413 A3 20061025**; DE 102005001067 A1 20060720

DOCDB simple family (application)  
**EP 05111728 A 20051206**; DE 102005001067 A 20050107