

Title (en)

Insulation element for the inner surface of a building opening

Title (de)

Wärmedämmelement für die Laibung von Gebäudeöffnungen

Title (fr)

Élément d'isolation pour la surface intérieure d'une ouverture d'un bâtiment

Publication

**EP 1683925 A1 20060726 (DE)**

Application

**EP 06000632 A 20060112**

Priority

DE 102005001913 A 20050114

Abstract (en)

Heat insulating element comprises a base component (12) lying next to a window frame (8) inserted into a window opening (6) or a door frame inserted into a door opening, a plate-like heat insulating component (14) and a cleaning strip (16) fixed to the base component and sitting on the transition between the window frame or door frame and the base component in the assembled state. Preferred Features: The base component has a channel recess on its rear side which is open to the gap between the window frame or door frame and a soffit. Connecting channels (30) are arranged along the base component between a front surface of the base component and the inside of the channel recess.

IPC 8 full level

**E04B 1/76** (2006.01)

CPC (source: EP)

**E04B 1/7641** (2013.01); **E06B 1/62** (2013.01); **E06B 1/58** (2013.01); **E06B 2001/624** (2013.01)

Citation (search report)

- [X] DE 19857383 A1 20000621 - ROCKWOOL MINERALWOLLE [DE]
- [X] DE 9107425 U1 19911017

Cited by

EP3106578A1; US11761258B1; US12116828B2

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

**EP 1683925 A1 20060726; EP 1683925 B1 20100908**; AT E480677 T1 20100915; DE 102005001913 A1 20060810; DE 502006007805 D1 20101021

DOCDB simple family (application)

**EP 06000632 A 20060112**; AT 06000632 T 20060112; DE 102005001913 A 20050114; DE 502006007805 T 20060112