

Title (en)

Device for avoiding damage to hangings

Title (de)

Vorrichtung zur Verhinderung von Schäden an Behängen

Title (fr)

Dispositif de prévention de dommages à des volets

Publication

**EP 1686231 B1 20120725 (DE)**

Application

**EP 05405648 A 20051118**

Priority

CH 522005 A 20050114

Abstract (en)

[origin: EP1686231A1] Device for preventing damage to a blind or shutter comprises a coupling (17) having a sleeve (19) enclosing a lifting shaft. The sleeve is connected to a lifting wheel (5) for the blind or shutter and a coupling unit (23) connected to the lifting shaft is inserted into the sleeve. The coupling unit produces a connection between the lifting shaft and the lifting wheel when the scallop is lowered and raised and the connection is broken when a force acts against the rotary movement of the lifting wheel. The coupling unit axially moves on the lifting shaft using a helical element (31). Preferred Features: The coupling unit comprises a peripheral screw path which interacts between the threads of the helical element.

IPC 8 full level

**E06B 9/322** (2006.01)

CPC (source: EP)

**E06B 9/322** (2013.01)

Cited by

EP2549051A1; EP2085564A2

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

**EP 1686231 A1 20060802; EP 1686231 B1 20120725; ES 2393960 T3 20130103**

DOCDB simple family (application)

**EP 05405648 A 20051118; ES 05405648 T 20051118**