

Title (en)
LOCK

Title (de)
SCHLOSS

Title (fr)
SERRURE

Publication
EP 1687501 B1 20071107 (DE)

Application
EP 04720603 A 20040315

Priority
• EP 2004002669 W 20040315
• DE 10361929 A 20031121

Abstract (en)
[origin: WO2005052291A1] The invention relates to a lock which can be used for doors which are fitted on the right or left. Said lock comprises a nut which can be adjusted from the outside by an actuating element and which is disposed in a housing. Said lock enables a bolt to be displaced between a closed position, i.e. when it is pushed out from the housing, and an open position, which is when it is pushed into the housing, by means of an adjusting element. According to the invention, the bolt is maintained in a closed position, counter to the pretension of a spring, in order to enable said type of lock, which can be optionally used on the left or on the right, to be produced without any additional costs, and that the nut can be adjusted from the pushed out bolt (closed position), optionally, in a clockwise direction or in an anti-clockwise direction, in order to move the bolt into an open position.

IPC 8 full level
E05C 1/16 (2006.01); **E05B 65/44** (2006.01); **E05C 9/08** (2006.01)

CPC (source: EP US)
E05C 1/16 (2013.01 - EP US); **E05C 9/066** (2013.01 - US); **E05C 9/08** (2013.01 - EP US); **Y10T 292/0839** (2015.04 - EP US); **Y10T 292/0845** (2015.04 - EP US); **Y10T 292/1097** (2015.04 - EP US)

Designated contracting state (EPC)
DE FR GB IT NL

DOCDB simple family (publication)
DE 10361929 A1 20050630; AU 2004292578 A1 20050609; DE 502004005454 D1 20071220; EP 1687501 A1 20060809; EP 1687501 B1 20071107; US 2007080545 A1 20070412; US 7384079 B2 20080610; WO 2005052291 A1 20050609

DOCDB simple family (application)
DE 10361929 A 20031121; AU 2004292578 A 20040315; DE 502004005454 T 20040315; EP 04720603 A 20040315; EP 2004002669 W 20040315; US 58018204 A 20040315