

Title (en)

DISPLAY DEVICE WITH A WHITE-OPTIMIZING BISTABLE NEMATIC SCREEN AND METHOD FOR THE DEFINITION OF SAID DEVICE

Title (de)

DISPLAY-EINRICHTUNG MIT EINEM WEISSOPTIMIERENDEN BISTABILEN NEMATISCHEN SCHIRM UND VERFAHREN ZUR DEFINITION DER EINRICHTUNG

Title (fr)

DISPOSITIF D'AFFICHAGE A ECRAN DE TYPE NEMATIQUE BISTABLE OPTIMISANT LE BLANC ET PROCEDE DE DEFINITION DE CE DISPOSITIF

Publication

**EP 1690130 A1 20060816 (FR)**

Application

**EP 04805550 A 20041125**

Priority

- FR 2004003021 W 20041125
- FR 0313991 A 20031128

Abstract (en)

[origin: WO2005054940A1] The invention relates to a nematic liquid crystal display having two stable states, without an electric field, obtained by anchoring break, characterized in that it comprises two polarizers (10, 40), one(10) of which is placed on the observer side, the other (40) being placed on the opposite side of the liquid crystal cell whereby the latter is at least partially reflecting in order to define a reflective mode or transreflective mode. The orientation of the two polarizers (10, 40) is offset by a value which is equal to the rotatory power of the cell at approximately +/- 30 DEG .

IPC 8 full level

**G02F 1/139** (2006.01)

CPC (source: EP KR US)

**G02F 1/1335** (2013.01 - KR); **G02F 1/139** (2013.01 - KR); **G02F 1/1391** (2013.01 - EP US)

Citation (search report)

See references of WO 2005054940A1

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LU MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

**FR 2863061 A1 20050603; FR 2863061 B1 20060224**; CN 100541303 C 20090916; CN 1997934 A 20070711; EP 1690130 A1 20060816; JP 2007512561 A 20070517; JP 5230859 B2 20130710; KR 101265335 B1 20130520; KR 20060115906 A 20061110; TW 200527039 A 20050816; TW I406028 B 20130821; US 2007103619 A1 20070510; US 7532275 B2 20090512; WO 2005054940 A1 20050616

DOCDB simple family (application)

**FR 0313991 A 20031128**; CN 200480034961 A 20041125; EP 04805550 A 20041125; FR 2004003021 W 20041125; JP 2006540535 A 20041125; KR 20067012872 A 20060627; TW 93136390 A 20041126; US 58032004 A 20041125