

Title (en)

Print gap detector, liquid ejecting apparatus incorporating the same, and print gap detecting method executed in the apparatus

Title (de)

Druckabstanddetektor, Flüssigkeitsausstossvorrichtung welche einen solchen beinhaltet, und durch die Vorrichtung ausgeführtes Druckabstandbestimmungsverfahren

Title (fr)

Détecteur d'espacement d'impression, dispositif d'éjection de liquide le comportant, et procédé de détection de l'espacement d'impression exécuté par le dispositif

Publication

EP 1690690 A2 20060816 (EN)

Application

EP 06002637 A 20060209

Priority

- JP 2005032922 A 20050209
- JP 2005181796 A 20050622

Abstract (en)

A gap detector is operable to detect a distance between a liquid ejecting head adapted to eject liquid toward a target medium and a platen adapted to support the target medium. A circular plate is adapted to be provided on a guide shaft which is rotated together with the rotary plate to selectively determine the distance as one of a plurality of distances. The circular plate has a plurality of flags formed on an outer periphery, each of which is associated with one of the distances. A sensor is disposed in the vicinity of the outer periphery of the circular plate and operable to output a signal indicative of a passage of each of the flags in accordance with the rotation of the circular plate. At least one of intervals between the flags in a circumferential direction of the circular plate is made different from the other.

IPC 8 full level

B41J 25/308 (2006.01)

CPC (source: EP US)

B41J 3/4071 (2013.01 - EP US); **B41J 25/308** (2013.01 - EP US); **B41J 25/3088** (2013.01 - EP US)

Citation (applicant)

- JP 2002067428 A 20020305 - SEIKO EPSON CORP
- JP 2003211778 A 20030729 - SEIKO EPSON CORP
- JP 2004314591 A 20041111 - SEIKO EPSON CORP

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI SK TR

DOCDB simple family (publication)

EP 1690690 A2 20060816; **EP 1690690 A3 20090722**; US 2006193670 A1 20060831; US 7591602 B2 20090922

DOCDB simple family (application)

EP 06002637 A 20060209; US 34994406 A 20060209